

## 2A/40V ULTRA-LOW VF SURFACE MOUNT SCHOTTKY DIODE

These ultra-efficient, low VF Schottky diodes feature high current capability, while housed in a very small SOD-123 Flat Lead package. They are ideal for applications requiring maximum power dissipation per board area.

### FEATURES

- PN Guard-Ring Die Construction for Transient Protection
- High Current Capability
- Low  $V_F$  for Reduced Forward Conduction Loss
- Lead-Free Plating (100% Matte Tin Finish)



### APPLICATIONS

- Mobile Phones and Accessories
- Hand-Held Computers

MARKING CODE: GP

### MAXIMUM RATINGS $T_J = 25^\circ\text{C}$ Unless otherwise noted

Rating	Symbol	Value	Units
Repetitive Peak Reverse Voltage	$V_{RRM}$	40	V
Continuous Reverse Voltage	$V_R$	40	V
Continuous Forward Current	$I_{F(AV)}$	2.0	A
Non-repetitive Peak Forward Current, $t = 1\text{sec}$ , Square Wave	$I_{FSM}$	50	A
Total Power Dissipation (Note 1)	$P_{tot}$	550	mW
Operating Junction Temperature Range	$T_J$	-55 to +125	C
Storage Temperature Range	$T_{stg}$	-55 to +150	C

Note 1. FR-5 Board 1.0 x 0.75 x 0.062 in.




### THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Units
Thermal Resistance, Junction to Ambient	$R_{thja}$	181	$^\circ\text{C/W}$

**ELECTRICAL CHARACTERISTICS**  $T_J = 25^\circ\text{C}$  Unless otherwise noted


Parameter	Symbol	Conditions	Min	Typ	Max	Units
Breakdown Voltage (Note 1)	$V_{BR}$	$I_{BR} = 0.5\text{mA}$	40	-	-	V
Forward Voltage (Note 1)	$V_F$	$I_F = 1.0\text{A}$	-	0.4	0.45	V
		$I_F = 2.0\text{A}$	-	0.45	0.50	
		$I_F = 3.0\text{A}$	-	0.5	0.65	
Reverse Leakage Current (Note 1)	$I_R$	$V_R = 20\text{V}$	-	0.003	0.15	mA
		$V_R = 20\text{V}$ $T_J = 85^\circ\text{C}$	-	-	18	
		$V_R = 40\text{V}$	-	0.01	0.5	
Total Capacitance	$C_T$	$V_R = 40\text{V}$ $T_J = 85^\circ\text{C}$	-	-	25	pF
		10Vdc Bias, $f = 1\text{MHz}$	-	70	-	

Note 1. Short duration pulse to avoid self-heating effect.

**TYPICAL CHARACTERISTIC CURVES**




## PACKAGE LAYOUT AND SUGGESTED PAD DIMENSIONS



## ORDERING INFORMATION

SS2040FL T/R7 - 7 inch reel, 3K units per reel

SS2040FL T/R13 - 13 inch reel, 10K units per reel

## Copyright PanJit International, Inc 2005

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.