

Belt Paper Tag


EPC Class 1 Gen 2, ISO 18000-63

Impinj M730

Sales code 3007861

Mechanical dimensions

A1 x A2	Antenna size	70 x 14 mm	± 0,5 mm	2,756 x 0,551 in
B1 x B2	Die-cut size	73 x 17 mm	± 0,2 mm	2,874 x 0,669 in
C	Web width	80 mm	± 0,5 mm	3,150 in
D	Pitch, length per piece MD	20 mm	± 1,5 mm	0,787 in
E	Die-cut to web edge	3,5 mm	± 1,5 mm	0,138 in
U	Corner radius	3 mm		0,118 in
	Marking of bad ones	5x3 mm		0,197 x 0,118 in



Electrical characteristics

Integrated Circuit (IC)	Impinj M730
Air interface protocol	EPC Class 1 Gen 2, ISO 18000-63
Operation frequency	860 - 960 MHz
Memory	128 bit EPC


General characteristics of transponder

Operating temperature (electronics parts)	-40 °C / +85 °C	-40 °F / 185 °F
ESD voltage immunity	± 2 kV peak HBM	
Shelf life: From the date of manufacture 2 years in	+20 °C, 50 % RH	68 °F, 50 % RH
Bending diameter (D)	> 50 mm, tension less than 10 N	

Delivery form

Transponder format	Die-cut	
Transponder face material	Mid-gloss paper	
Transponder antenna material	Aluminum	
Transponder adhesive	RA-5	
- labelling temperature	min. +0 °C	min. 32 °F
- usage temperature	-20 °C - 80 °C	-4 °F - 176 °F
- peel	min. 10 N / 25 mm (FTM 1)	
Final inspection	100 %, known faulty ones marked	
Minimum delivery yield	97 %	
Reel Label	Reel number, Material number, Material description, Yield, Qty of functional inlays, Qty of non-functional inlays, Date	

Structure



Delivery details

Appearance	Single row reel form
Reel core	Paper core inner diameter 76 mm (3 in)
Winding of the reel	Face out
Reel size	5000 pcs/reel Diameter: max. OD 203,2MM/ 8"
Package size	10 000 pcs/box Deliveries only in full packages.

Disclaimer:

SMARTRAC reserves the right to change its products and services at any time without notice. Our recommendations are based on our best knowledge and experience. As the products are used outside our control we cannot take responsibility for any damage that may be caused when using the product. Use extra care in handling the product.

This technical specification replaces all earlier ones.

Version 1
 Update date 5 December 2020
 Author SMARTRAC /
 Approved SMARTRAC / 07/12/2020 MHasani

