

COMP C SUBWOOFERS

Model	Size (cm)	Impedance	Continuous Power Handling (Watts Peak/RMS)	Sensitivity (1W,1m)	Outer Frame Dimension(cm)	Mounting Cutout(cm)	Mounting Depth(cm)	Frequency Response	Min/Max Recommended Sealed Box Vol.(L)	Min/Max Recommended Vented Box Vol.(L)	Price (個) CWC S/D
CWCS/D84	20	4Ω svc/4Ω dvc	400/200	85.6	21.2	17.7	9.8	30Hz-500Hz	14.2-34	18.7-34	¥19,000/¥21,000 (本体価格)
CWCS/D104	25	4Ω svc/4Ω dvc	500/250	86.2	26.6	23.3	12.2	30Hz-500Hz	28.3-68	35.4-49.6	¥23,000/¥25,000 (本体価格)
CWCS/D124	30	4Ω svc/4Ω dvc	600/300	88.3	31.2	27.9	13.8	27Hz-500Hz	35.4-99.1	49.6-63.7	¥28,000/¥30,000 (本体価格)
CWCS/D154	38	4Ω svc/4Ω dvc	1200/600	90.3	38.6	35	17.8	25Hz-500Hz	63.7-141.6	85-113.3	¥36,000/¥38,000 (本体価格)