

RAYQUAL MOUNT ADAPTER PRODUCT LINEUP

as of March, 2022

Regarding product name e.g.: The adapter to attach Leica M mount lenses to the Sony α E mount body
 LM - S α E . T Tripod mount symbol
 Lens mount product symbol Body mount product symbol

○ : Standard type T : The tripod mount cannot be removed due to the emphasis on robustness.

For 35mm lens adapter			Body											
Lens with an aperture ring Yes/No	Body mount		SONY α E	FUJI FX	Micro 4/3	EOS M	Nikon Z	EOS R	Leica L	Leica M *3	EOS Single-lens reflex	Pentax K	FUJI GFX	
	Lens mount	Symbol	S α E	FX	M4/3	EFM	NZ	EOSR	LA	LM	EOS	PK	GFX	
Yes *1	Leica M	LM	○	○	○	○	○	○	○					
	Leica L39	L39	○*5	○*5	○*5					LtoM ring				
	Canon FD	FD	○	○	○	○	○	○	○	○			○*6	
	Nikon F	NF	○	○	○	○	○	○	○	○	○		○*6	
	Olympus OM	OM	○	○	○	○	○	○	○	○	○		○*6	
	Leica R	LR	○	○	○	○	○	○	○	○	○		○*6	
	CONTAX/Yashica	CY	○	○	○	○	○	○	○	○	○		○*6	
	Pentax K	PK	○	○	○	○	○	○	○	○	○		○*6	
	M42	M42	○*5	○*5	○*5	○	○	○	○	○	○	○		○*6
	EXAKTA	EXA	○	○	○	○	○	○	○	○				○*6
	Minolta MD	MD	○	○	○		○	○		○				
	Konica AR	KAR	○	○			○	○		○				
	CONTAX C/Nikon S (outer claw)	SC	○	○	○	○	○	○	○	○				
Asahiflex	ASHM37	○					○	○						
No *2	Nikon F (G) *4	NFG	○	○	○	○					○			
	Pentax DA	PDA	○	○	○	○					○			
	SONY/Minolta α	S α												
	Others													

Others			Body										
Lens with an aperture ring Yes/No	Body mount		SONY α E	FUJI FX	Nikon Z	EOS R	Leica M *3	EOS Single-lens reflex	Nikon F	Pentax K	M42	Pentax 645	FUJI GFX
	Lens mount	Symbol	S α E	FX	NZ	EOSR	LM	EOS	NF	PK	M42	P645	GFX
No *2	Deckel	DKL	○	○			○	○	○		○		
Yes *1	Leica VISOFLEX lens II - III type	VISO	○	○	○	○	○	○	○				
	HASSELBLAD V system	HS	T	T				○		○		○	T
	Pentax 645	P645	T										T

Note 1: Lens with an aperture operation ring on the lens unit.

Note 2: Lens without an aperture operation ring on the lens unit. An aperture operation mechanism is required on the lens adapter.

Note 3: Adapters other than the L-M ring are not interlocked with the rangefinder. The focusing shall be adjusted by visual measurement. (Excluding the models incorporated with the live view function, such as the Leica M type 240.)

Note 4: Not compatible with E Type lenses equipped with an electromagnetic aperture mechanism.

Note 5: ".ADJ" is added to the tail of the product name of those types with the lens stopper position adjuster (ADJ type).

Restrictions when using our adapter

- Automatic focusing function cannot be used. Focusing is manual.
- Use the camera with A-Mode (aperture priority) or M-Mode (Manual). The exposure metering will be stopped-down aperture metering.
- Aperture operation cannot be done from the camera side. The aperture is operated on the lens side.
- Shake prevention function from the lens side cannot be used.
- Lens name, focal length, and aperture data are not recorded in EXIF information.