


3 ダクト用換気扇

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
10 cm	* DVF-10G	'74	9,800	75	66	φ 100	202 × 232	273	197 × 222	189	131	117.5	104.5	—	—	—	—		●DVF-T10L (格子形) ●注意：埋込寸法など異なる
	廃 止	'76																	
	* DVF-10S	'76	9,800	75	66	φ 100	175	225	170	178.5	126.5	69.5	100.5	—	—	—	—		
	* DVF-10S ₂	'79	9,800 11,100	84	69	φ 100	175	225	170	187	122	68.5	101.5	—	—	—	—		DVF-T10L (格子形)
	DVF-10F	'85	10,800	84	69	φ 100	175	225	168	199	119	84	84	212	—	162	222		
	DVF-10F ₂	'90	10,800 11,800	84	69	φ 100	175	225	168	197	118.5	84	84	212	—	168	226		
	廃 止	'02																	
	DVF-10J (ホワイト) DVF-10JA (ベージュ)	'85	11,800	84	69	φ 100	175	230	168	197	118.5	84	84	212	—	162	222		
	DVF-10J ₂ (ホワイト) DVF-10JA ₂ (ベージュ)	'90	11,800 12,800	84	69	φ 100	175	230	168	197	118.5	84	84	212	—	168	226		
	DVF-G10V (シルキーホワイト)	'95	12,800	94	96	φ 100	175	230	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₃	'02	12,800	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₄	'08	13,600	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₈	'09	15,000	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-T10L	'17	15,000 17,200 19,800	90	90	φ 100	175	246	170 (171)	185	119.5	85.5	85.5	204	204	—	146	P.149	
	DVF-10JB (ホワイト) DVF-10JAB (ベージュ)	'86	14,500	84	69	φ 100	175	230	168	200	119	84	84	212	—	162	222		
	DVF-10JB ₂ (ホワイト) DVF-10JAB ₂ (ベージュ)	'89	14,500	84	69	φ 100	175	230	168	200	119	84	84	212	—	162	222		
	DVF-10JB ₃ (ホワイト) DVF-10JAB ₃ (ベージュ)	'91	14,500 15,500	84	69	φ 100	175	230	168	197	118.5	84	84	212	—	168	226		
	DVF-G10VB (シルキーホワイト)	'98	16,000	94	96	φ 100	175	230	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₃ B	'06	16,000	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₃ B ₁	'16	18,600	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-T10LB	'19	19,800 22,700 26,100	90	90	φ 100	175	246	170 (171)	185	119.5	85.5	85.5	204	204	—	146	P.224	2極接地形差込みプラグ
	DVF-10JS	'90	15,800 17,000	84	69	φ 100	175	230	168	197	118.5	84	84	212	—	168	226		
	DVF-G10VS	'95	18,000	94	96	φ 100	175	230	168	195	119.5	84	84	204	204	—	146		
	DVF-G10VS ₄	'08	20,200 23,200 31,700 36,500	94	96	φ 100	175	230	168	195	119.5	84	84	204	204	—	146	P.154	
	DVF-10BXK	'93	23,000	84	69	φ 100	175	254	168	170	89	84	84	—	—	—	—		
	DVF-G10CBK ₃	'08	23,000	77	77	φ 100	175	254	168	185	120	84	84	—	—	—	—		●DVF-T10CB 結露センサーなし
	廃 止	'13																	
	DVF-10B DVF-10BX	'88	12,800 13,800	72	75	φ 100	175	254	168	170	89	84	84	—	—	—	—		
	DVF-G10B	'95	13,500	94	96	φ 100	175	254	168	185	120	84	84	204	204	—	146		
	DVF-G10CB ₃	'02	13,500	85	87	φ 100	175	254	168	185	120	84	84	204	204	—	146		
	DVF-G10CB ₄	'08	14,300	85	87	φ 100	175	254	168	185	120	84	84	204	204	—	146		
	DVF-T10CB	'14	15,000 15,200 16,300 18,700	89	89	φ 100	175	254	171 (171.5)	185	107.5	86	86	204	204	—	146	P.136	
	DVF-XT10C DV-X10B 別売ルーバー	'13	13,400 14,300 16,400 2,100 2,800 3,100	89	89	φ 100	175	254	171 (171.5)	185	107.5	86	86	204	204	—	146	P.177	
	DVF-G10CBD ₃	'02	17,500	94 50	96 50	φ 100	175	254	168	185	120	84	84	204	204	—	146		
	DVF-XT10CDA DV-X10B 別売ルーバー	'13	16,100 16,400 17,300 19,900 2,100 2,800 3,100	89 59	89 59	φ 100	175	254	171 (171.5)	185	107.5	86	86	204	204	—	146	P.178	
	DVF-G10CBDA ₃	'04	17,500	94 30	96 30	φ 100	175	254	168	185	120	84	84	204	204	—	146		
	DVF-XT10CDK DV-X10B 別売ルーバー	'13	16,100 16,400 17,300 19,900 2,100 2,800 3,100	89 35	89 35	φ 100	175	254	171 (171.5)	185	107.5	86	86	204	204	—	146	P.179	
	DVF-10HX	'89	12,800 13,800	94	75	φ 100	175	244	168	170	89	84	84	—	—	—	—		
	DVF-G10H	'95	13,000	84	96	φ 100	175	244	168	185	120	84	84	204	204	—	146		
	DVF-G10CL ₃	'02	13,000	85	87	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-G10CL ₄	'08	13,800	85	87	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-T10CL	'13	14,300 14,500 15,600 17,900	91	91	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.135	
	DVF-XT10C DV-X10L 別売ルーバー	'13	13,400 14,300 16,400 1,900 2,300 2,500	91	91	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.177	
	DVF-G10CLE ₃	'02	21,000	85	87	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-G10CLE ₄	'08	22,300	85	87	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-T10CL DV-10CES 別売品	'13	14,300 14,500 15,600 17,900 8,500 9,400 10,300	91	91	φ 100	175	246	171 (171.5)	185	120	86	86	204	204	—	146	P.135	●廃止機種の排気口を残し本 体のみ買替取付も可能

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
10 cm	DVF-G10CLDA ₃	'03	17,000	85 60	87 60	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-XT10CDA DV-X10L 別売ルーバー	'13	16,100 16,400 17,300 19,900 1,900 2,300 2,500	91 60	91 60	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.178	
	DVF-G10CLDK ₃	'04	17,000	85 30	87 30	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-XT10CDK DV-X10L 別売ルーバー	'13	16,100 16,400 17,300 19,900 1,900 2,300 2,500	91 35	91 35	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.179	
	DVF-10BXB 廃 止 (フラットパネル)	'90 '93	15,500 16,500	72	75	φ 100	175	254	168	170	89	84	84	—	—	—	—		DVF-T10CLB 又は DVF-T10CLBH (格子形)
	DVF-10HXB	'90	15,500 16,500	72	75	φ 100	175	244	168	170	89	84	84	—	—	—	—		
	DVF-G10HB	'98	16,200	94	96	φ 100	175	244	168	185	120	84	84	204	204	—	146		
	DVF-G10CL ₃ B	'06	16,200	85	87	φ 100	175	246	168	185	120	84	84	204	204	—	146		
	DVF-T10CLB	'16	17,900 19,600 22,500	91	91	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.221	2 極接地形差込みプラグ
	DVF-T10CLBH	'16	20,000 21,700 25,000	91	91	φ 100	175	246	171 (171.5)	185	107.5	86	86	204	204	—	146	P.221	2 極接地形差込み引掛プラグ
	DVF-10JX (ホワイト) DVF-10JXA (ベージュ)	'88	12,800	72	65	φ 100	175	230	168	197	118.5	84	84	212	—	162	222		
	DVF-10JX ₂ (ホワイト) DVF-10JXA ₂ (ベージュ)	'90	12,800 13,800	94	65	φ 100	175	230	168	197	118.5	84	84	212	—	168	226		
	DVF-G10V (シルキーホワイト)	'95	12,800	94	96	φ 100	175	230	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₃	'02	12,800	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₄	'08	13,600	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-G10L ₈	'09	15,000	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVF-T10L	'17	15,000 17,200 19,800	90	90	φ 100	175	246	171 (171.5)	185	119.5	85.5	85.5	204	204	—	146	P.149	
	DVF-10U, 10UB, 10USBKCT 廃 止	'98 '06	— (特注品)	85	85	φ 100	175	256	168	170	97	84	84	204	—	—	146		●DVF-T10CB ●本体高さ、本体カバー取付方法が異なる
	DVF-XT10	'17	13,600 15,400 17,700	—	—	φ 100	175	—	170 (171)	185	119.5	85.5	85.5	204	204	—	146	P.187	●別売ルーバー(本体カバー)が必要
	DVF-10CHK ₆	'18	25,200 26,100 30,000	90	95	φ 100	180	250	174	184	102	87	87	206	—	122	—	P.140	
丸穴取付φ200	DVF-C10C	'98	13,000	65	85	φ 100 φ 200 φ 260	168.5 × 175	200	110	90	90	—	—	—	—	—	—		
	DVF-A10C	'99	12,700	85	85	φ 100 φ 200 φ 260	170	197	125	85	85	204	219	—	146				
	DVF-A10C ₄	'08	13,500 14,500 15,400 17,700	85	85	φ 100 φ 200 φ 260	170	197	125	85	85	204	219	—	146	P.143			
	DVF-C10K	'98	13,000	85	85	φ 100 φ 200	244 168.5 × 175	200	110	90	90	—	—	—	—	—	—		
	DVF-A10K	'99	12,700	85	85	φ 100 φ 200	244	170	197	125	85	85	204	219	—	146			DVF-A10K・A10K ₄ は角穴 (□175) でも取付可能
	DVF-A10K ₄	'08	13,500 14,500 15,400 17,700	85	85	φ 100 φ 200	244	170	197	125	85	85	204	219	—	146	P.143		
	DVF-A10KC ₄	'09	14,500 15,500 16,400 18,900	85	85	φ 100 φ 200	244	170	197	125	85	85	204	219	—	146	P.143		DVF-A10KC ₄ は角穴 (□175) でも取付可能
	DVF-S10V	'95	12,800	85	91	φ 75	175	230	168	197	119.5	84	84	204	204	—	146		
	DVF-S10V ₁	'97	12,300	88	91	φ 75	175	230	168	197	119.5	84	84	204	204	—	146		
	DVF-S10V ₄	'08	13,100 15,000 17,200 19,800	88	91	φ 75	175	230	168	197	119.5	84	84	204	204	—	146	P.157	
細管形	DVF-S10H	'95	13,000	88	91	φ 75	175	244	168	185	120	84	84	204	204	—	146		
	DVF-S10H ₁	'97	12,500	88	91	φ 75	175	244	168	185	120	84	84	204	204	—	146		
	DVF-S10H ₄	'08	13,300 14,500 15,600 17,900	88	91	φ 75	175	244	168	185	120	84	84	204	204	—	146	P.156	
	DVF-13CHK ₆	'18	28,000 28,700 33,000	125	130	φ 100	215	286	204	195	107	102	102	236	—	122	—	P.140	
14 cm	DVF-14Z	'80	11,900 12,800	100	88	φ 100	175	230	168	204	135	84	84	208	—	—	221		DVF-T10L (シロッコファン)
	DVF-14ZC (ブラウン) 廃 止 (ターボファン)	'80 '93	11,900 12,800	100	88	φ 100	175	230	168	204	135	84	84	208	—	—	221		DVF-T10L (ムーンホワイト・シロッコファン)
	DVF-14ZBL (アイボリー) DVF-14ZCBL (ブラウン)	'81	14,500	98	89	φ 100	175	230	168	204	135	84	84	208	—	—	221		DVF-T10LB (ムーンホワイト・シロッコファン)
	DVF-14JS 廃 止 (BL品・ターボファン)	'90	18,800	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14VS	'95	19,500 21,000 24,200 35,300 40,600	190	184	φ 100	225	280	217	195.5	119.5	108.5	108.5	253	253	—	146	P.154	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
14 cm	DVF-14JSS	'93	41,000	168	162	φ 100	225	310	217	200	107.5	108.5	108.5	—	—	—	—		
	廃 止	'97																	
	DVF-14JP (高静圧タイプ)	'89	16,800	186	186	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		DVF-T14LQ (大風量形)
	廃 止	'89																	
	DVF-14JBP (高静圧タイプ)	'89	17,800	186	186	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		DVF-T14CLQDB (コード線 3m 付)
	廃 止	'90																	
	DVF-14J (ホワイト) DVF-14JA (ベージュ)	'85	13,000	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14J₂ (ホワイト) DVF-14JA₂ (ベージュ)	'90	13,000 14,800	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14V (シルキーホワイト)	'95	14,800	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₃	'02	14,800	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₄	'08	16,000	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₆	'09	17,600	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14L	'17	18,400 21,100 24,300	183	180	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.149	
	* DVF-14GD	'73	11,000	168	180	φ 100	202 × 232	273	197 × 222	182	124	176	46	—	—	—	—		
	廃 止	'80		138	144														
	* DVF-14BL	'80	16,900 18,200	164	155	φ 100	225	270	220	199.5	134.5	50.5	169.5	260	—	—	209.5		
	DVF-14JB (ホワイト) DVF-14JAB (ベージュ)	'86	18,200	180	174	φ 100	225	280	217	200	50.5	108.5	108.5	265	138	164	222		
	DVF-14JB₂ (ホワイト) DVF-14JAB₂ (ベージュ)	'89	18,200	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JB₃ (ホワイト) DVF-14JAB₃ (ベージュ)	'89	18,200 19,200	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14VB (シルキーホワイト)	'98	20,300	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14LD₃B (シルキーホワイト)	'06	20,300	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14LD₃B₁ (シルキーホワイト)	'16	24,500	170	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14LDB (ムーンホワイト)	'19	24,500 28,200 32,400	183	188	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.224	3 極接地形差込みプラグ
	* DVF-14X	'78	15,800	120	120	φ 100	225	270	220	193	135	50.5	169.5	—	—	—	—		
	* DVF-14X₂	'79	15,800 18,000	120	120	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
	DVF-14JX (ホワイト) DVF-14JXA (ベージュ)	'85	15,000	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JX₂ (ホワイト) DVF-14JXA₂ (ベージュ)	'90	15,000 16,000	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14V (シルキーホワイト)	'95	14,800	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₃	'02	14,800	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₄	'08	16,000	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₆	'09	17,600	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14L	'17	18,400 21,100 24,300	183	180	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.149	
	DVF-14JQ	'85	17,700	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JQ₂	'90	17,700 19,000	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14VQ	'95	17,800	225	216	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14LQ₃	'02	17,800	212	206	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14LQ₄	'08	18,900	212	206	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14LQ₆	'09	20,800	212	206	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14LQ	'17	20,800 23,900 27,500	218	216	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.149	
	DVF-14JQA (ベージュ)	'85	17,700	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JQA₂ (ベージュ)	'90	17,700 19,000	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		DVF-T14LQ (ムーンホワイト)
	廃 止	'93																	
	* DVF-18BL	'83	19,800	185	185	φ 100	275	322.5	270	198.5	133.5	61.5	208.5	311	—	—	227		●DVF-18BL は、アタッチメント (DV-18A) を使用し、DVF- T14CLQDB にて代替。 ●DVF-T14LDB (風量注意)
	DVF-14JQB (ホワイト) DVF-14JQAB (ベージュ)	'87	19,800	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JQB₂ (ホワイト) DVF-14JQAB₂ (ベージュ)	'89	19,800	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14JQB₃ (ホワイト) DVF-14JQAB₃ (ベージュ)	'91	19,800 21,100	216	216	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14VQB (シルキーホワイト)	'98	22,200	205	200	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	廃 止	'07																	
	DVF-14FQ	'85	14,000	216	216	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14FQ₂	'90	14,000 16,000	216	216	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		DVF-T14LQ (大風量形)
	廃 止	'02																	
	* DVF-14A	'71	6,200	144	168	φ 100	198 × 228	240	194 × 219	170	121	171	48	—	—	—	—		
	廃 止	'73																	
	* DVF-14G	'73	11,000	144	150	φ 100	202 × 232	273	197 × 222	182	124	176	46	—	—	—	—		●DVF-T14L (格子形) ●注意：埋込寸法など異なる
	廃 止	'76																	
	* DVF-14S	'76	11,000	144	144	φ 100	225	270	220	193.5	135.5	50.5	169.5	—	—	—	—		
	* DVF-14S₁	'77	11,000	144	144	φ 100	225	270	220	193	135	50.5	169.5	—	—	—	—		
	* DVF-14S₂	'79	11,000 12,500	144	144	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
	DVF-14F	'85	12,500	180	174	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		DVF-T14L (格子形)
	DVF-14F₂	'90	12,500 13,800	180	174	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	廃 止	'02																	
	DVF-G14V	'95	14,800	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₃	'02	14,800	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₄	'08	16,000	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14L₆	'09	17,600	175	170	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14L	'17	18,400 21,100 24,300	183	180	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.149	

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
14 cm	* DVF-14SM	'76	11,500	144	144	φ 100	225	270	220	193.5	135.5	50.5	169.5	—	—	—	—		
	* DVF-14SM ₁	'77	11,500	144	144	φ 100	225	270	220	192.5	135	50.5	169.5	—	—	—	—		
	* DVF-14SM ₂	'79	11,500 13,000	144	144	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
	* DVF-14SM ₃	'82	13,000	144	144	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
	DVF-14M	'85	14,800	180	174	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14M ₂	'90	14,800 15,800	180	174	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14M	'95	16,800 18,500	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14M ₈	'09	20,400	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14M	'18	21,400 23,900 27,500	181	178	φ 100	225	280	219.5 (220)	200	119.5	110	110	253	253	—	146	P.172	
	* DVF-14SS	'76	15,800	114	114	φ 100	225	270	220	193.5	135.5	50.5	169.5	—	—	—	—		
	* DVF-14SS ₁	'77	15,800	114	114	φ 100	225	270	220	192.5	135	50.5	169.5	—	—	—	—		
	* DVF-14SS ₂	'79	15,800 18,200	114	114	φ 100	225	270	220	192.5	134.5	50.5	169.5	—	—	—	—		
	* DVF-14XM ₃	'82	18,200	114	114	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
	DVF-14MX	'85	18,200	138	132	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14MX ₂	'90	18,200	138	132	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MRX	'93	16,800	180	174	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14M	'95	16,800 18,500	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14M ₈	'09	20,400	190	184	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14M	'18	21,400 23,900 27,500	181	178	φ 100	225	280	219.5 (220)	200	119.5	110	110	253	253	—	146	P.172	
	DVF-14MK	'88	14,800	171	165	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14MK ₂	'91	14,800 16,800	171	165	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MRK	'93	17,800 19,600	171	165	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MRK ₈	'09	21,600 23,500 27,000	171	165	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226	P.158	
	DVF-14MKQ	'88	16,800	171	165	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MKQ ₂	'91	16,800 19,000	171	165	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MRKQ	'93	19,000 20,900	216	206	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-14MRKQ ₈	'09	22,800 23,600 27,100	216	206	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226	P.158	
	DVF-14EX DVF-14EXC	'85	18,800	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222		
	DVF-14EX ₂ DVF-14EXC ₂	'90	18,800	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226		
	DVF-G14R	'95	17,800 18,500	162	162	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14R ₈	'09	20,400	162	162	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14RV	'17	18,600 21,200 24,400	183	180	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.152	
	DVF-G14RC	'95	18,800 19,500	162	162	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14RC ₈	'09	21,400	162	162	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-XT14 DV-X14RV(T) 別売ルーバー	'17	16,900 18,500 21,300 2,200 2,900 3,200	183	180	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.189	
	DVF-G14RX ₈	'09	16,200	135	135	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14RVX	'17	18,500 20,700 23,800	150	153	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.152	
	DVF-G14RQ	'95	19,800	212	212	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-T14RVQ	'17	21,000 24,900 28,600	218	216	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.152	
	DVF-G14RQC	'95	19,800 20,800	212	212	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-XT14Q DV-X14RV(T) 別売ルーバー	'17	19,300 22,100 25,400 2,200 2,900 3,200	218	216	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.190	
	DVF-G14RDA ₃	'03	21,800 24,000	162 70	162 70	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14RDA ₈	'09	25,900	162 70	162 70	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-XT14D DV-X14RV 別売ルーバー	'17	23,200 24,800 28,500 2,200 2,900 3,200	183 110	188 106	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.192	
	DVF-G14RDAC ₃	'03	20,800 25,100	162 70	162 70	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14RDAC ₈	'09	26,900	162 70	162 70	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-XT14D DV-X14RV(T) 別売ルーバー	'17	23,200 24,800 28,500 2,200 2,900 3,200	183 110	188 106	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.192	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考		
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d				
14 cm	DVF-G14RDX ₈	 '09	18,400	138 84	138 79.5	φ 100	225	283	217	198	119.5	108.5	108.5	253	253	—	146		P.191		
	DVF-XT14DX DV-X14RV 別売ルーバー	 '17	22,000 25,300 2,200 2,900 3,200	150	153	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146				
	DVF-14WX DVF-14WXC	 '85	18,800	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	164	222	● DVF-XT14+DV-X14RV(T) (インテリア格子、ブラウン)			
	DVF-14WX ₂ DVF-14WXC ₂	 '90	18,800	138	132	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226				
	DVF-G14W DVF-G14WC	 '95	18,800 20,700	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146				
	DVF-G14W ₂ DVF-G14WC ₂	 '09	22,800 23,800	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146				
	廃 止	'18																			
	DVF-14B	 '89	13,800 14,800	174	168	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		P.138		
	DVF-G14B	 '95	15,500	190	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CB ₃	 '02	15,500	186	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CB ₄	 '08	16,400	186	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-T14CB	 '14	18,000 18,300 18,600 21,400	181	180	φ 100	225	310	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.138		P.181	
	DVF-XT14C DV-X14B 別売ルーバー	 '12	16,300 17,100 19,700 2,200 3,200 3,500	181	180	φ 100	225	310	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146				
	DVF-14BB	 '90	15,000 16,900	174 108	168 108	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		DVF-T14CLDKB 又は DVF-T14CLDKBH (格子形)		
	DVF-14BB ₂	 '93	18,000	174 108	168 108	φ 100	225	310	217	210	109	108.5	108.5	255	226	—	211				
	DVF-G14BB	 '98	21,300	190 90	184 90	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	廃 止	'07																			
	DVF-14BQ	 '89	17,700 18,900	210	210	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		P.182		
	DVF-G14BQ	 '95	17,500	225	216	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CBQ ₃	 '02	17,500	216	216	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CBQ ₄	 '08	18,500	216	216	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-XT14CQ DV-X14B 別売ルーバー	 '12	17,300 17,400 18,100 20,800 2,200 3,200 3,500	209	209	φ 100	225	310	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.182		DVF-T14CLQDB (格子形、風量)	
	DVF-14BQB	 '90	19,800 21,000	210 120	210 120	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—				
	DVF-14BQB ₂	 '93	22,100	180 114	180 114	φ 100	225	310	217	210	109	108.5	108.5	255	226	—	211				
	DVF-G14BQB	 '98	23,300	205 100	200 100	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	廃 止	'07																			
	DVF-14BX	 '89	17,800 19,000	144	144	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		P.138		
	DVF-G14B	 '95	15,500	190	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CB ₃	 '02	15,500	186	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CB ₄	 '08	16,400	186	184	φ 100	225	310	217	198	120	108.5	108.5	243	243	—	146				
	DVF-T14CB	 '14	18,000 18,300 18,600 21,400	181	180	φ 100	225	310	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.138		P.181	
	DVF-XT14C DV-X14B 別売ルーバー	 '12	16,300 17,100 19,700 2,200 3,200 3,500	181	180	φ 100	225	310	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146				
	DVF-14BXB (フラットパネル)	 '90	19,900 21,100	144 102	144 102	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		DVF-T14CLDKB 又は DVF-T14CLDKBH (格子形)		
	廃 止	'93																			
	DVF-14BXS (結露・人感センサー付)	 '89	29,800	144	144	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		DVF-T14CB (結露・人感センサーなし)		
	廃 止	'93																			
	DVF-14BXK	 '93	26,500	144	144	φ 100	225	310	217	205	109	108.5	108.5	—	—	—	—		DVF-T14CB (結露センサーなし)		
	DVF-G14CBK ₃	 '08	26,500	168	168	φ 100	225	310	217	198	120	108.5	108.5	—	—	—	—				
	廃 止	'13																			
	DVF-G14CLX ₄	 '09	16,200	140	145	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146			P.137	
	DVF-T14CLX	 '12	16,200 16,900 18,500 21,300	152	155	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146				
	DVF-14H	 '89	13,800 14,800	174	168	φ 100	225	290	217	205	109	108.5	108.5	—	—	—	—		P.137		
	DVF-14HX	 '89	17,800 19,000	144	144	φ 100	225	290	217	205	109	108.5	108.5	—	—	—	—				
	DVF-G14H	 '95	15,000	190	184	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CL ₃	 '02	15,000	186	184	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CL ₄	 '08	15,900	186	184	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-T14CL	 '12	17,300 17,900 19,000 21,900	188	185	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.137			
	DVF-14HQ	 '90	17,700 18,900	210	210	φ 100	225	293	217	205	109	108.5	108.5	—	—	—	—		P.137		
	DVF-G14HQ	 '93	17,000	225	216	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CLQ ₃	 '98	17,000	216	216	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-G14CLQ ₄	 '08	18,000	216	216	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146				
	DVF-T14CLQ	 '12	18,400 19,300 20,400 23,500	223	220	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.137			

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
14 cm	DVF-14HB	'89	15,900 16,900	174 108	168 108	φ 100	225	290	217	205	109	108.5	108.5	—	—	—	—		
	DVF-14HB ₂	'95	18,000	174 108	168 108	φ 100	225	293	217	210	109	108.5	108.5	—	—	—	—		
	DVF-G14HB	'98	20,800	182 96	182 93	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-G14CLD ₃ B	'06	20,800	170 92	170 85	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-T14CLDKB	'16	23,800 24,900 28,600	190 117	190 113	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	3 極接地形差込みプラグ
	DVF-T14CLDKBH	'16	26,100 27,200 31,300	190 117	190 113	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	3 極接地形差込み引掛プラグ
	DVF-14HQB	'90	19,800 21,000	210 120	210 120	φ 100	225	293	217	205	109	108.5	108.5	—	—	—	—		
	DVF-14HQB ₂	'93	22,100	180 114	180 114	φ 100	225	293	217	210	109	108.5	108.5	—	—	—	—		
	DVF-G14HQB	'98	22,800	196 106	196 100	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-G14CLQD ₃ B	'06	22,800	180 103	180 95	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-T14CLQDB	'16	25,300 27,200 31,300	205 135	206 130	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	3 極接地形差込みプラグ
	DVF-G14CLE ₃	'02	23,000	186	184	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-G14CLE ₄	'08	24,800	186	184	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-T14CL DV-14CES 別売品	'12	17,300 17,900 19,000 21,900 8,500 9,400 10,300	188	185	φ 100	225	293	219.5 (223.0)	200	120	111.5	111.5	243	243	—	146	P.137	●廃止機種の排気口を残し 本体のみ買替取付も可能
	DVF-G14CLQE ₃	'02	25,000	216	216	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-G14CLQE ₄	'08	26,500	216	216	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-T14CLQ DV-14CES 別売品	'12	18,400 19,300 20,400 23,500 8,500 9,400 10,300	223	220	φ 100	225	293	219.5 (223.0)	200	120	111.5	111.5	243	243	—	146	P.137	●廃止機種の排気口を残し 本体のみ買替取付も可能
	DVF-G14CLDA ₃	'03	19,000	186 75	184 75	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-XT14CDA DV-X14L 別売ルーバー	'12	18,800 19,300 20,000 23,000 2,000 2,700 3,000	190 86	190 78	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.184	
	DVF-G14CLDK ₃	'04	19,000	186 110	184 110	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-XT14CDK DV-X14L 別売ルーバー	'12	18,800 19,300 20,000 23,000 2,000 2,700 3,000	190 117	190 113	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.185	
	DVF-G14CLQD ₃	'09	20,100	200 135	200 125	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-XT14CQD DV-X14L 別売ルーバー	'12	20,300 20,700 21,400 24,600 2,000 2,700 3,000	205 135	206 130	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.186	
	DVF-XT14CDX	'12	17,300 18,400 19,400 22,300	—	—	φ 100	225	—	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.183	●別売ルーバー(本体カバー)が必要
	DVF-TD14CLD	'12	32,800 34,800 40,000	280 160	280 160	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.130	
	DVF-XTD14CD	'12	31,800 33,800 38,900	—	—	φ 100	225	—	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.131	●別売ルーバー(本体カバー)が必要
	DVF-14HXB	'90	19,900 21,100	144 102	144 102	φ 100	225	293	217	205	109	108.5	108.5	—	—	—	—		
	DVF-14HXB ₂	'93	21,100	144 102	144 102	φ 100	225	293	217	210	109	108.5	108.5	—	—	—	—		
	DVF-G14HB	'98	20,800	182 96	182 93	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-G14CLD ₃ B	'06	20,800	170 92	170 85	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVF-T14CLDKB	'16	23,800 24,900 28,600	190 117	190 113	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	3 極接地形差込みプラグ
	DVF-T14CLDKBH	'16	26,100 27,200 31,300	190 117	190 113	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	3 極接地形差込み引掛プラグ
	* DVF-18ZP (ターボファン)	'85	17,700	120	123	φ 100	225	280	218	218	144	109	109	258	—	—	235		
	DVF-14P ₂	'91	17,700 18,900	144	144	φ 100	225	280	217	210	107.5	108.5	108.5	265	138	168	226		
	DVF-G14P	'95	19,800 21,800	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-G14P ₈	'09	24,000	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
	DVF-XT14 DV-X14P 別売ルーバー	'17	16,900 18,500 21,300 8,100 8,900	179	176	φ 100	225	280	219.5 (220)	200	119.5	110	110	253	253	—	146	P.189	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考	
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d			
14 cm	* DVF-18ZPC(ターボファン)	'85	17,700	120	123	φ 100	225	280	218	218	144	109	109	258	—	—	235	DVF-XT14+DV-X14P (シルキーホワイト)		
	DVF-14PC ₂	'91	17,700 18,900	144	144	φ 100	225	280	217	210	107.5	108.5	108.5	265	138	168	226			
	DVF-G14PC	'95	19,800 21,800	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146			
	DVF-G14PC _s	'09	24,000	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146			
	廃 止	'13																		
	DVF-G14PQ	'95	21,800	212	212	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		DVF-T14LQ (ルーバーデザイン違い)	
	廃 止	'07																		
	DVF-14FPX	'93	20,800	154	150	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226	P.189		
	DVF-G14FP	'95	19,800 21,800	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146			
	DVF-G14FP _s	'09	24,000	162	162	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146			
	DVF-XT14 DV-X14FV 別売ルーバー	'17	16,900 18,500 21,300 6,400 7,500 8,300	170	170	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146			
	DVF-14FPQX	'93	22,800	200	200	φ 100	225	280	217	200	107.5	108.5	108.5	265	138	168	226			
	DVF-G14FPQ	'95	21,800	212	212	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		DVF-T14LQ (ルーバーデザイン違い)	
	廃 止	'07																		
	DVF-G14FPDX _s	'09	18,400	123 76	127 72	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146	P.191		
	DVF-XT14DX DV-X14FV 別売ルーバー	'17	22,000 25,300 6,400 7,500 8,300	140 82	144 78	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146			
	DVF-G14FPDA ₃	'03	23,800 26,200	162 70	162 70	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146			
	DVF-G14FPDA _s	'09	28,800	162 70	162 70	φ 100	225	280	217	198	119.5	108.5	108.5	253	253	—	146		P.192	
	DVF-XT14D DV-X14FV 別売ルーバー	'17	23,200 24,800 28,500 6,400 7,500 8,300	167 104	175 101	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146			
	DVF-14FXK	'93	24,600	154	150	φ 100	225	280	217	200	107.5	108.5	108.5	—	—	—	—			
	DVF-14FXK ₄	'08	26,100	154	150	φ 100	225	280	217	200	107.5	108.5	108.5	—	—	—	—			
	DVF-14FXK _s	'09	28,700	154	150	φ 100	225	280	217	200	107.5	108.5	108.5	—	—	—	—			
	廃 止	'18																		
	DVF-T14CLXB	'16	22,500 24,900 28,600	152	155	φ 100	225	293	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.222	2 極接地形差込みプラグ	
	DVF-XT14CX	'12	15,300 15,500 16,800 19,300	—	—	φ 100	225	—	219.5 (223.0)	200	107.5	111.5	111.5	243	243	—	146	P.180	●別売ルーバー(本体カバー)が必要	
	DVF-XT14X	'17	16,800 18,000 20,700	—	—	φ 100	225	—	219.5 (220)	200	119.5	110	110	253	253	—	146	P.188	●別売ルーバー(本体カバー)が必要	
	DVF-XT14QD	'17	24,200 26,100 30,000	—	—	φ 100	225	—	219.5 (220)	200	119.5	110	110	253	253	—	146	P.193	●別売ルーバー(本体カバー)が必要	
	DVF-T14FVX	'17	22,700 24,400 28,100	140	144	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.153		
	DVF-T14FVQ	'17	25,200 28,700 33,000	195	198	φ 100	225	293	219.5 (220)	200	119.5	110	110	253	253	—	146	P.153		
	* DVL-14A	'72	12,600	120	132	φ 100	198 × 228	270	194 × 219	170	121	171	48	—	—	—	—	● DVL-14KX ₄ ● 注意：埋込寸法など異なる ● 照明器具は別売		
	* DVL-14A ₁	'75	16,000	120	132	φ 100	198 × 228	270	194 × 219	170	121	171	48	—	—	—	—			
	廃 止	'76																		
	* DVL-14S	'76	17,500	144	144	φ 100	225	270	220	193.5	135.5	50.5	169.5	—	—	—	—	照明器具は別売		
	* DVL-14S ₁	'77	17,500	144	144	φ 100	225	270	220	192.5	135	50.5	169.5	—	—	—	—			
	* DVL-14S ₂	'79	17,500 19,700	144	144	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—			
	* DVL-14S ₃	'85	21,400 23,500	174	168	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222			
	DVL-14KX	'90	19,800 21,800	132	132	φ 100	225	300	217	205	109	108.5	108.5	—	—	—	—			
	DVL-14KX ₄	'08	24,200 27,000 33,000 38,000	150	150	φ 100	225	300	217	205	109	108.5	108.5	—	—	—	—			P.142
DVF-C14C	'98	15,000	130	130	φ 100	φ 250	φ 310	206	200	110	100.5	100.5	—	—	—	—	P.143			
DVF-A14C	'99	14,700	141	141	φ 100	φ 250	φ 310	220	198	125	110	110	256	237	—	146				
DVF-A14C ₄	'08	15,900 16,900 17,800 20,500	141	141	φ 100	φ 250	φ 310	220	198	125	110	110	256	237	—	146				
DVF-C14K	'98	15,000	130	130	φ 100	φ 250	293	206	200	110	100.5	100.5	—	—	—	—	DVF-A14K ₄ は角穴 (□225)でも取付可能	P.143		
DVF-A14K	'99	14,700	141	141	φ 100	φ 250	293	220	198	125	110	110	256	237	—	146				
DVF-A14K ₄	'08	15,900 16,900 17,800 20,500	141	141	φ 100	φ 250	293	220	198	125	110	110	256	237	—	146				
DVF-A14KC	'99	15,700	141	141	φ 100	φ 250	293	220	198	125	110	110	256	237	—	146		DVF-A14KC ₄ は角穴 (□225)でも取付可能	P.143	
DVF-A14KC ₄	'08	16,900 17,900 18,800 21,600	141	141	φ 100	φ 250	293	220	198	125	110	110	256	237	—	146				

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考	
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d			
14 cm	細 管 形	DVF-S14V	'95	14,800	165	165	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-T14L+DV-07KT (片落管)にて代替	
		DVF-S14V ₁	'97	13,800	165	165	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14VQ	'95	17,800	195	191	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-T14LQ+DV-07KT (片落管)にて代替	
		DVF-S14VQ ₁	'97	16,800	195	191	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14VP	'95	22,000	190	185	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-T14LQ+DV-07KT (片落管)にて代替	
		DVF-S14VP ₁ (鋼板ボディ)	'97	19,800	190	185	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14H	'96	15,000	165	165	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146	P.156	
		DVF-S14H ₁	'97	14,000	165	165	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
		DVF-S14H ₄	'08	14,800 17,000 21,100 24,300	165	165	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
		DVF-S14HQ	'96	17,000	191	195	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146	●排気口を残し、本体・化粧 枠をDVF-T14CLQにて代替	
		DVF-S14HQ ₁	'97	16,000	191	195	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
		廃 止	'07																	
		DVF-S14HP	'96	22,000	190	185	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146	●排気口を残し、本体・化粧 枠をDVF-TD14CLDにて代替	
		DVF-S14HP ₁	'97	19,000	190	185	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
		廃 止	'07																	
		DVF-S14R	'96	17,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-T14RV+DV-07KT (片落管)にて代替	
		DVF-S14R ₁	'97	16,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14RC	'96	17,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-XT14+DV-X14RV(T) +DV-07KT (片落管)にて代替	
		DVF-S14RC ₁	'97	16,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14FP	'95	19,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146	●DVF-T14RV+DV-07KT (片落管)にて代替	
		DVF-S14FP ₁	'97	18,800	141	141	φ 75	225	280	217	198	119.5	108.5	108.5	253	253	—	146		
		廃 止	'07																	
		DVF-S14MRKQ	'97	18,500	187	190	φ 75	225	280	217	200	107.5	108.5	108.5	265	138	168	226	●排気口を残し、本体・化粧 枠をDVF-14MRKQ8にて代替	
		廃 止	'07																	
18 cm		* DVF-18ZW (ターボファン)	'81	18,800	151.8	157.2	φ 100	225	280	218	218	144	109	109	258	—	—	235	●DVF-XT14+DV-X14RV (T) (シロッコファン・ルーバーデ ザイン違い)	
		廃 止	'85																	
		* DVF-18S	'82	18,800	192	180	φ 100	275	322.5	270	199	134	62	209	—	—	—	—	●アタッチメント (DV-18A) を使用し、DVF-T14CLQにて代 替 (プラスチックボディ)	
		廃 止	'85																	
		* DVF-18BL	'83	19,800	185	185	φ 100	275	322.5	270	198.5	133.5	61.5	208.5	311	—	—	227	●アタッチメント (DV-18A) を使用し、DVF-T14CLQDB にて代替 (プラスチックボ ディ)	
		廃 止	'87																	
		DVF-18Z (ターボファン)	'80	13,100 14,800	152	157	φ 100	225	280	218	218	144	109	109	258	—	—	235	●DVF-T14L (シロッコファン)	
		廃 止	'00																	
		DVF-18ZC (ブラウン) (ターボファン)	'80	13,100 14,800	152	157	φ 100	225	280	218	218	144	109	109	258	—	—	235	●DVF-XT14+DV-X14RV(T) (シロッコファン)	
		廃 止	'93																	
		DVF-18ZBL・18ZCBL (BL品) (ターボファン)	'81	18,100	142.2	154.2	φ 100	225	280	218	218	144	109	109	258	—	—	235	●DVF-T14LDB (ムーンホワイト・シロッコ ファン)	
		廃 止	'89																	
		DVF-18J ₂	'91	15,300 19,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
		DVF-18L ₃	'01	19,800 21,800	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
		DVF-18L ₈	'09	24,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.162	
		DVF-T18L	'16	26,800 28,300 32,500	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
		DVF-18JXS	'01	28,800 33,000 40,600 46,700	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.154	DVF-T18L
		* DVF-18X	'77	18,800	246	240	φ 150	275	322.5	270	216.5	133.5	66	204	—	—	—	—		
		* DVF-18X ₂	'79	18,800 20,500	246	240	φ 150	275	322.5	270	214.5	124.5	66	204	—	—	—	—		
		DVF-18JX DVF-18JXA	'85	18,000	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	185.5	243		
		DVF-18JX ₂ DVF-18JXA ₂	'91	18,000 21,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
		廃 止	'01																	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考		
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d				
18 cm	DVF-18JXY	'90	23,800	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	185.5	243				
	DVF-18JXY ₂	'91	23,800 25,500	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	205	263				
	DVF-18LY ₃	'01	25,500 27,300	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18LY ₈	'09	30,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18LY	'16	30,000 33,700 38,800	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.150			
	* DVF-18XS	'81	20,500	248	240	φ 150	275	322.5	268	251	140	66	204	—	—	—	—				
	DVF-18EX	'85	21,500	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	185.5	243				
	DVF-18EX ₂	'91	21,500 23,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18R	'95	23,800	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18R ₃	'01	23,800 24,500	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18R ₈	'09	27,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18RV	'16	27,000 28,500 32,800	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	206			P.163	
	DVF-18EXC	'85	21,500	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	185.5	243				
	DVF-18EXC ₂	'91	21,500 23,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		●大風量タイプもあります。 本体：DVF-XT18Q		
	DVF-18RC	'95	24,800	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RC ₃	'01	24,800 25,500	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RC ₈	'09	28,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-XT18 DV-X18RV(T) 別売ルーバー	'15	23,900 28,300 32,500 4,100 4,600 5,100	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.199			
	DVF-18RDA ₃	'03	24,800 25,500	300 140	280 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RDA ₈	'09	28,000	300 140	280 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18RVDA	'16	30,300 34,100 39,200	305 145	295 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263			P.163	
	DVF-18RDAC ₃	'03	25,800 26,500	300 140	280 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RDAC ₈	'09	29,000	300 140	280 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-XT18DA DV-X18RV(T) 別売ルーバー	'15	27,200 31,600 36,300 4,100 4,600 5,100	305 145	295 130	φ 150	275	330	270	240	128.5	77	193	314	—	205	263			P.202	
	DVF-18RS ₃	'07	21,500	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RS ₈	'09	23,600	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18RVS	'16	23,600 25,100 28,900	235	230	φ 100	275	330	270	240	128.5	77	193	314	—	205	263	P.161			
	DVF-18RCS ₃	'07	23,900	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RCS ₈	'09	24,600	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-XT18S DV-X18RV(T) 別売ルーバー	'16	20,500 23,500 27,000 4,100 4,600 5,100	235	230	φ 100	275	330	270	240	128.5	77	193	314	—	205	263			P.198	
	* DVF-20ZW	'81	21,400	234	240	φ 150	275	330	268	251	146	134	134	308	—	—	251				
	DVF-18WX	'85	21,500	270	270	φ 150	275	330	270	260	128.5	77	193	314	—	185.5	243				
	DVF-18WX ₂	'91	21,500 23,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18WR	'95	24,800	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	185.5	243				
	DVF-18W ₃	'01	24,800 27,300	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18W ₈	'09	30,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18WC ₈	'09	31,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-XT18 DV-X18W 別売ルーバー	'16	23,900 28,300 32,500 7,100 8,200 9,000	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	263			P.199	
	DVF-XT18 DV-X18W(T) 別売ルーバー	'16	23,900 28,300 32,500 7,100 8,200 9,000	305	295	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.199			
	DVF-18P	'85	20,400	249	246	φ 150	275	320	269 × 270	254	129	67.5	202.5	309	—	—	244		●フラットインテリア パネルタイプ DVF-T18FV もあります。		
	DVF-18PC	'91	21,500 24,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18P ₂	'01	24,000 26,400	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18P ₃	'09	29,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18P	'16	31,200 35,000 40,300	290	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.170			
	DVF-18PC ₈	'09	29,000	300	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		DVF-T18P (ムーンホワイト)		
	廃 止	'13																			
	DVF-18PS ₃	'07	25,000	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18PS ₈	'09	27,400	200	200	φ 100	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-XT18S DV-X18P 別売ルーバー	'16	20,500 23,500 27,000 8,300 9,000 9,900	230	225	φ 100	275	330	270	240	128.5	77	193	314	—	205	263	P.198			
	DVF-18RQ	'95	26,800	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RQ ₃	'01	26,800 27,500	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-18RQ ₈	'09	30,300	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263				
	DVF-T18RVQ	'16	30,300 32,300 37,100	335	320	φ 150	275	330	270	240	128.5	77	193	314	—	205	263			P.163	風量小

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d		
18 cm	DVF-18RQC	'95	27,800	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.200	風量小
	DVF-18RQC ₃	'01	27,800 28,500	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18RQC ₈	'09	31,300	350	340	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-XT18Q DV-X18RV(T) 別売ルーバー	'16 '15	27,200 28,600 32,900 4,100 4,600 5,100	335	320	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18RQD ₃	'01	27,800 28,500	350 240	340 230	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.163	風量小
	DVF-18RQD ₈	'09	31,400	350 240	340 230	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-T18RVQD	'16	34,800 37,400 43,000	335 320 215	320 205	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18FPNQ	'93	42,800	320	310	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	●本体寸法にて代替 ●DVF-T20FV ●消音構造無し、騒音注意	
	DVF-18FPNQ ₃	'01	42,800 47,100	350	330	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-18FPNQ ₈	'09	51,800	350	330	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	廃 止 (消音形)	'16																	
	DVF-18FPX	'93	24,800	270	270	φ 150	275	335	270	240	128.5	77	193	314	—	185.5	243	P.167	
	DVF-18FP ₃	'01	24,800 27,300	300	280	φ 150	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-18FP ₈	'09	30,000	300	280	φ 150	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-T18FV	'16	31,200 33,200 38,200	290	280	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18FPDA ₃	'03	25,800 28,400	300 140	280 130	φ 150	275	335	270	240	128.5	77	193	314	—	205	263	P.167	
	DVF-18FPDA ₈	'09	31,200	300 140	280 130	φ 150	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-T18FVDA	'16	34,500 36,900 42,400	290 135	280 125	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18FPS ₃	'07	25,000	200	200	φ 100	275	335	270	240	128.5	77	193	314	—	205	263	P.161	
	DVF-18FPS ₈	'09	27,400	200	200	φ 100	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-T18FVS	'16	27,800 29,800 34,300	230	225	φ 100	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18FPQX	'93	29,800	330	318	φ 150	275	335	270	240	128.5	77	193					P.167	風量小
	DVF-18FPQ ₃	'01	29,800 31,700	350	330	φ 150	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-18FPQ ₈	'09	34,900	350	330	φ 150	275	335	270	240	128.5	77	193	314	—	205	263		
	DVF-T18FVQ	'16	34,500 36,900 42,400	320	300	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	* DVF-19A	'71	8,200	366	372	φ 150	258 × 284	320	254 × 274	196	123	210.5	63.5	—	—	—	—	●DVF-18MRKQ ₈ ●注意：埋込寸法など異なる	
	* DVF-20G	'73	16,500	330	330	φ 150	317 × 322	362	312	221	138	243.5	68.5	—	—	—	—		
	廃 止	'76																	
	* DVF-18SM	'76	13,600	318	306	φ 150	275	320	270	216.5	133.5	66	204	—	—	—	—		
	* DVF-18SM ₂	'79	13,600 15,300	318	306	φ 150	275	320	270	230	140	66	204	—	—	—	—	P.159	
	* DVF-18SM ₃	'82	15,300	318	306	φ 150	275	320	270	230	140	66	204	—	—	—	—		
	DVF-18MQ	'85	15,300	330	318	φ 150	275	320	270	260	128.5	77	193	314	—	185.5	243		
	DVF-18MKQ ₂	'91	17,800 21,800	330	324	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18MRKQ	'93	21,800	330	324	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18MRKQ ₂	'02	21,800 24,000	345	330	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	DVF-18MRKQ ₆	'08	24,000	345	330	φ 150	275	330	268	239	128.5	76	192	314	—	205	263		
	DVF-18MRKQ ₈	'09	26,400 30,800 35,400	345	330	φ 150	275	330	268	239	128.5	76	192	314	—	205	263		
	DVF-18MRKS ₂	'02	20,800	270	260	φ 100	275	330	270	240	137	73	197	314	—	205	263	P.158	
	DVF-18MRKS ₅	'05	20,800 22,900	270	260	φ 100	275	330	270	240	137	73	197	314	—	205	263		
	DVF-18MRKS ₆	'08	22,900	270	260	φ 100	275	330	268	239	136	70	198	314	—	205	263		
	DVF-18MRKS ₈	'09	25,200 28,400 32,700	270	260	φ 100	275	330	268	239	136	70	198	314	—	205	263		
	* DVF-18XM	'81	21,500	246	240	φ 150	275	320	270	230	140	66	204	—	—	—	—	●DVF-18MRKQ ₈ ●羽根：金属製 ●風量	
	* DVF-18XM ₃	'82	21,500	246	240	φ 150	275	323	270	230	140	66	204	—	—	—	—		
	DVF-18MX	'85	21,500	270	270	φ 150	275	320	270	260	128.5	77	193	314	—	185.5	243		
	DVF-18MX ₂	'91	21,500 23,000	270	270	φ 150	275	320	270	240	128.5	77	193	314	—	205	263		
	DVF-18MRX	'93	23,000	270	270	φ 150	275	330	270	240	128.5	77	193	314	—	205	263		
	廃 止	'01																	
	DVF-18CH ₃	'02	27,800	300	300	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	145	—	P.139	
	DVF-18CH ₄	'06	27,800	300	300	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	145	—		
	DVF-18CH ₅	'13	30,200	320	310	φ 150	316	390	310	240	135	69	241	341	200 210	145	—		
	DVF-18CH ₆	'18	30,200 34,700	320	310	φ 150	316	390	310	240	135	69	241	341	200 210	145	—		

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	吐出 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d		
18 cm	DVF-D18L	'13	47,800	430 300 180	430 300 180	φ 150	280	335	270 (276)	243	135	71	205	304	200	—	207		
	DVF-D18RV	'18	47,800 55,000	430 300 180	430 300 180	φ 150	280	335	270 (276)	243	135	68	202	304	200	—	207	P.134	
	DVF-XT18Y	'15	27,100 30,100 34,600	—	—	φ 150	275	—	270	240	128.5	77	193	314	—	205	263	P.194	●別売ルーバー(本体カバー)が必要
	DVF-XT18QD	'16	31,700 33,100 38,100	—	—	φ 150	275	—	270	240	128.5	77	193	314	—	205	263	P.201	●別売ルーバー(本体カバー)が必要
	DVF-T18FVQD	'16	39,000 42,000 48,300	320 205	300 195	φ 150	275	330	270	240	128.5	77	193	314	—	205	263	P.167	
	DVF-20Z	'80	15,300 18,000	234	240	φ 150	275	330	268	234	146	134	134	308	—	—	251		●DVF-T18L(シロッコファン) ●浴室設置の場合は、 DVF-T18LY
	廃 止 (ターボファン)	'00																	
	DVF-20ZC	'80	15,300 18,000	234	240	φ 150	275	330	268	234	146	134	134	308	—	—	251		●DVF-XT18+DV-X18RV(T) ●浴室設置の場合は、 DVF-T18LY
廃 止 (ブラウン・ターボファン)	'93																		
20 cm	* DVF-20X	'77	26,800	360	348	φ 150	316	363	311.5	219.5	136.5	66.7	244.8	—	—	—	—		
	* DVF-20X₂	'79	28,800 30,800	360	348	φ 150	316	363	311.5	219.5	136.5	66.7	244.8	—	—	—	—		
	DVF-20JX (シルキーホワイト) DVF-20JXA (ベージュ)	'85	22,000 24,500	324	330	φ 150	316	370	309	264	128.5	77	232	356	—	185.5	243		
	DVF-20JRX (シルキーホワイト)	'93	27,000	375	375	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20L₃	'01	27,000 29,700	400	400	φ 150	316	380	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20L₈	'09	32,700	400	400	φ 150	316	380	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20L	'16	35,000 37,700 43,400	460	455	φ 150	316	380	311	255	131	69.5	241.5	356	—	213	271	P.162	
	DVF-20JY	'90	28,800 30,800	408 300	396 294	φ 150	316	370	309	261.5	128.5	77	232	356	—	185.5	243		
	DVF-20JRY	'93	30,800	420 375	405 375	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20LYD₃	'01	30,800 33,900	400 280	400 260	φ 150	316	380	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20LYD₈	'09	37,300	400 280	400 260	φ 150	316	380	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20LYDA	'16	41,800 46,600 53,600	420 205	415 200	φ 150	316	380	311	255	131	69.5	241.5	356	—	213	271	P.150	風量小
	* DVF-20XS	'81	28,000	360	348	φ 150	316	363	311.5	227	137	66.7	244.8	—	—	—	—		
	DVF-20EX	'85	25,500 27,300	324	330	φ 150	316	370	309	264	128.5	77	232	356	—	185.5	243		
	DVF-20ERX	'93	29,800	375	375	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20R	'95	30,800	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20R₃	'01	30,800 32,000	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20R₈	'09	35,200	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20RV	'16	35,200 37,800 43,500	460	455	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.164	
	DVF-20EXC	'85	25,500 27,300	324	330	φ 150	316	370	309	264	128.5	77	232	356	—	185.5	243		
	DVF-20ERXC	'93	29,800	375	375	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RC	'95	31,800	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RC₃	'01	31,800 33,000	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RC₈	'09	36,300	400	400	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-XT20 DV-X20RV(T) 別売ルーバー	'15	31,900 35,400 40,700 4,300 4,800 5,300	460	455	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.203	
	DVF-20RQ DVF-20RQC	'95	35,800 36,800	500 400	500 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RQD₃	'01	35,800 37,000	500 400	500 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RQD₈	'09	40,700	500 400	500 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20RVQD	'16	40,700 43,300 49,800	520 410	515 400	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.164	
	DVF-20RQDC₃	'01	36,800 38,000	500 400	500 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RQDC₈	'09	41,800	500 400	500 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-XT20QD DV-X20RV(T) 別売ルーバー	'15	37,400 39,000 44,900 4,300 4,800 5,300	520 410	515 400	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.206	
	* DVF-20XM	'81	31,000	360	348	φ 150	316	360	311.5	226.5	137	66.7	244.8	—	—	—	—		
	* DVF-20XM₃	'82	31,000	360	348	φ 150	316	360	311.5	227	137	66.7	244.8	—	—	—	—		
	DVF-20MX	'85	31,000	330	330	φ 150	316	359	309	264	128.5	77	232	356	—	185.5	243		
	DVF-20MRX	'93	31,000 34,100	360	360	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20MRX₈	'09	37,500 43,100	360	360	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	P.159	
	* DVF-20SM	'76	16,600	426	420	φ 150	316	360	311.5	219.5	136.5	66.7	244.8	—	—	—	—		
	* DVF-20SM₂	'79	16,600 19,200	426	420	φ 150	316	360	311.5	227	137	66.7	244.8	—	—	—	—		
	* DVF-20SM₃	'82	19,200	426	420	φ 150	316	360	311.5	227	137	66.7	244.8	—	—	—	—		
	DVF-20M	'85	19,300 21,800	432	414	φ 150	316	359	309	264	128.5	77	232	356	—	185.5	243		
	DVF-20MR	'93	24,800 27,300	432	432	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20MR₈	'09	30,000 32,500 36,500 42,000	432	432	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	P.159	
	DVF-20MQ	'85	28,500 31,800	516 324	504 300	φ 150	316	359	309	270.5	128.5	77	232	356	—	185.5	243		
	DVF-20MRQ	'93	30,800 33,900	520 324	500 324	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20MRQ₈	'09	37,300 39,700 43,600 50,100	520 324	500 324	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	P.159	

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
20 cm	* DVF-20GD	'73	18,500	426	420	φ 150	317 × 322	362	312	221	138	243.5	68.5	—	—	—	—	● DVF-20MQHB ● 注意：埋込寸法など異なる	
	廃 止	'76																	
	* DVF-20SMH	'77	16,600	426	420	φ 150	316	360	311.5	219.5	136.5	244.8	66.7	—	—	—	—	DVF-20MQHB	
	* DVF-20SMH ₂	'79	16,600 19,200	426	420	φ 150	316	360	311.5	227	137	244.8	66.7	—	—	—	—		
	* DVF-20SMH ₃	'82	19,200	426	420	φ 150	316	363	311.5	227	137	244.8	66.7	—	—	—	—		
	* DVF-20MH (左排気)	'85	19,300 21,800	432	414	φ 150	316	359	309	264	128.5	232	77	356	—	185.5	243		
	廃 止	'93																	
	* DVF-20MQH (左排気)	'85	28,500 31,800	516 324	504 300	φ 150	316	359	309	270.5	128.5	232	77	356	—	185.5	243	● DVF-20MQHB ● 風量(強)：480/456	
	廃 止	'93																	
	* DVF-20G	'73	16,500	330	330	φ 150	317 × 322	362	312	221	138	243.5	68.5	—	—	—	—	● DVF-18MRKQ ₃ ● 注意：埋込寸法など異なる	
	廃 止	'78																	
	DVR-20GD	'74	22,000	330 246	336 252	φ 150	—	—	—	—	—	—	—	—	—	—	—	—	● 露出形 ● 幅324 × 奥行400 × 高さ200 (mm)
	廃 止	'78																	
	* DVF-20BL	'78	28,000 31,800	444 300	450 300	φ 150	316	360	311.2	260.5	132.6	84	227.5	352	—	—	230.6		
	* DVF-20BLM ₃	'82	31,800	444 300	450 300	φ 150	316	363	311.2	260.5	132.6	84	227.5	352	—	—	230.6		
	DVF-20MQB	'86	31,800 35,100 38,600 44,400 50,300 57,800	480 282	456 270	φ 150	316	359	309	270.5	128.5	77	232	356	—	185.5	243	P.226	
	* DVF-20BL ₂	'78	28,000 31,800	444 300	450 300	φ 150	316	360	311.2	260.5	132.6	227.2	84	352	—	—	230.6		
	* DVF-20BLH ₃	'82	31,800	444 300	450 300	φ 150	316	363	311.2	260.5	132.6	227.2	84	352	—	—	230.6		
	DVF-20MQHB	'86	31,800 35,100 38,600 44,400 50,300 57,800	480 282	456 270	φ 150	316	359	309	270.5	128.5	232	77	356	—	185.5	243	P.226	
	DVF-20P (シルキーホワイト) 20PC (ブラウン)	'85	31,800 32,800	432 318	399 294	φ 150	316	418	311	261.5	129	68	243	354	—	—	244	● フラットインテリアパネルタイプ DVF-T20FVD もあります。	
	DVF-20PR (シルキーホワイト)	'93	33,800	408 252	408 252	φ 150	316	418	309	255	130	68.5	240.5	354	—	213	271		
	DVF-20PD ₃	'01	33,800 37,200	400 280	400 260	φ 150	316	418	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20PD ₈	'09	40,900	400 280	400 260	φ 150	316	418	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20PD	'16	41,400 44,000 50,600	405 290	405 285	φ 150	316	418	311	255	131	69.5	241.5	356	—	213	271		P.170
	DVF-20FPX	'93	35,800	420 267	420 250	φ 150	316	370	309	255	255	68.5	240.5	356	—	213	271	風量・騒音注意	
	DVF-20FPD ₃	'01	35,800 39,400	400 280	400 260	φ 150	316	370	309	255	255	68.5	240.5	356	—	213	271		
	DVF-20FPD ₈	'09	43,300	400 280	400 260	φ 150	316	370	309	255	255	68.5	240.5	356	—	213	271		
	DVF-T20FVD	'16	41,400 43,400 49,900	400 280	400 270	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271		P.168
	DVF-20FPDA ₃	'03	35,800 39,400	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20FPDA ₈	'09	43,300	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	風量・騒音注意	
	DVF-T20FVDA	'16	43,600 45,600 52,400	400 195	400 190	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271		P.168
	DVF-20FPQX	'93	39,800	500 320	490 310	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	風量・騒音注意	
	DVF-20FPQD ₃	'01	39,800 43,800	500 400	490 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20FPQD ₈	'09	48,200	500 400	490 380	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20FVQD	'16	45,800 48,400 55,700	475 380	475 375	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.168	
	DVF-20FPN	'93	48,800	410 267	390 250	φ 150	363	420	358	274	152	94	264	403	—	223	280	● 本体寸法にて代替 ● DVF-XT23DA+DV-X23FV ● 消音構造無し、騒音注意	
	DVF-20FPND ₃	'01	48,800 53,700	410 267	390 250	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-20FPND ₈	'09	59,100	410 267	390 250	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	廃 止 (消音形)	'16																● 本体寸法にて代替 ● DVF-XT23DA+DV-X23FV ● 消音構造無し、騒音注意	
	DVF-20FPNQ	'93	52,800	486 312	456 288	φ 150	363	420	358	274	152	94	264	403	—	223	280		
	DVF-20FPNQD ₃	'01	52,800 58,100	500 400	490 380	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-20FPNQD ₈	'09	63,900	500 400	490 380	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	廃 止 (消音形)	'16																	
	DVF-20RD ₃	'01	31,800 33,000	400 280	400 260	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271	P.164	
	DVF-20RD ₈	'09	36,300	400 280	400 260	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20RVD	'16	36,300 40,800 46,900	420 295	415 290	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271		
	DVF-20RDA ₃	'03	31,800 33,000	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RDA ₈	'09	36,300	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-T20RVDA	'16	38,500 41,100 47,300	420 205	415 200	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.164	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考	
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d			
20 cm	DVF-20RDAC ₃		'03	32,800 34,000	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-20RDAC ₆		'09	37,400	400 180	400 170	φ 150	316	370	309	255	130	68.5	240.5	356	—	213	271		
	DVF-XT20DA DV-X20RV(T) 別売ルーバー		'15	35,200 37,300 42,900 4,300 4,800 5,300	420 205	415 200	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.205	
	DVF-20CH ₃		'02	35,500	400	380	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	—	145		
	DVF-20CH ₄		'06	35,500	400	380	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	—	145		
	DVF-20CH ₅		'13	38,600	420	400	φ 150	316	390	310	240	135	69	241	341	200 210	145	—		
	DVF-20CH ₆		'18	38,600 44,400	420	400	φ 150	316	390	310	240	135	69	241	341	200 210	145	—	P.139	
	DVF-20CHD ₄		'09	42,700	400 210	380 210	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	—	145		
	DVF-20CHD ₅		'13	42,700	420 210	400 210	φ 150	316	390	310	240	135	69	241	341	200 210	145	—		
	DVF-20CHD ₆		'18	42,700 49,100	420 210	400 210	φ 150	316	390	310	240	135	69	241	341	200 210	145	—	P.139	
	DVF-20CHK ₃		'02	44,300	400	380	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	—	145		
	DVF-20CHK ₄		'06	44,300	400	380	φ 150	316	390	302 × 303	240	135	66	237	341	200 210	—	145		
	DVF-20CHK ₅		'13	48,900	420	400	φ 150	316	390	310	240	135	69	241	341	200 210	145	—		
	DVF-20CHK ₆		'18	48,900 56,200	420	400	φ 150	316	390	310	240	135	69	241	341	200 210	145	—	P.141	
	DVF-D20L		'13	57,100	550 340	550 340	φ 150	316	380	307 (313)	243	135	70.5	242.5	341	200	—	207		
	DVF-D20RV		'18	57,100 65,700	550 340	550 340	φ 150	316	380	307 (313)	243	135	67.5	239.5	304	200	—	207	P.134	
	DVF-T20LY		'16	38,500 43,300 49,800	460	455	φ 150	316	380	311	255	131	69.5	241.5	356	—	213	271	P.150	
	DVF-T20RVQDA		'16	42,900 45,500 52,300	520 260	515 250	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.164	
	DVF-T20FV		'16	40,300 42,300 48,600	425	425	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.168	
	DVF-T20FVQDA		'16	48,000 50,100 57,600	475 240	475 230	φ 150	316	370	311	255	131	69.5	241.5	356	—	213	271	P.168	
	DVF-T20PQD		'16	45,800 48,400 55,700	500 400	495 390	φ 150	316	418	311	255	131	69.5	241.5	356	—	213	271	P.170	
	DVF-XT20Y		'16	34,400 39,700 45,700	—	—	φ 150	316	—	311	255	131	69.5	241.5	356	—	213	271	P.195	●別売ルーバー(本体カバー)が必要
	DVF-XT20YDA		'15	38,700 44,000 50,600	—	—	φ 150	316	—	311	255	131	69.5	241.5	356	—	213	271	P.196	●別売ルーバー(本体カバー)が必要
	DVF-XT20D		'16	33,000 36,200 41,600	—	—	φ 150	316	—	311	255	131	69.5	241.5	356	—	213	271	P.204	●別売ルーバー(本体カバー)が必要
	DVF-XT20QDA		'15	39,600 41,200 47,400	—	—	φ 150	316	—	311	255	131	69.5	241.5	356	—	213	271	P.207	●別売ルーバー(本体カバー)が必要
23 cm	DVF-23JQ (シルキーホワイト) DVF-23JQA (ベージュ)		'88	45,800	750 492	726 474	φ 150	363	420	358	289	129	86.2	271.8	403	—	185.5	243		●DVF-T23RVQDA ●大風量、強弱付
	DVF-23JRQ (シルキーホワイト)		'93	46,800	750 480	726 456	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	廃 止		'01																	
	DVF-23JX (シルキーホワイト) DVF-23JXA (ベージュ)		'88	38,000	480	468	φ 150	363	420	358	274	129	86.2	271.8	403	—	185.5	243		
	DVF-23JRX (シルキーホワイト)		'93	41,000	480	468	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-23RX ₃		'01	41,000 45,100	480	468	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-23RX ₆		'09	49,600	480	468	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-T23RVD		'16	48,400 52,700 60,600	635 500	580 465	φ 150	363	420	358	274	152	70	288	403	—	223	280	P.165	強弱付、弱運転で使用
	* DVF-23SM		'77	29,800	630 390	600 372	φ 150	363	410	358	275.5	130	86	272	394	288	—	230		
	* DVF-23SM ₂		'79	29,800 34,200	630 390	600 372	φ 150	363	410	358	275.5	129	86	272	394	288	—	230		
	* DVF-23SM ₃		'82	34,200	630 390	600 372	φ 150	363	410	358	275.5	129	86	272	394	288	—	230		
	DVF-23M		'85	34,200 36,600	678 426	648 414	φ 150	363	410	358	289	129	86.2	271.8	403	—	185.5	243		
	DVF-23MR		'93	39,800 43,800	690 450	664 450	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-23MR ₆		'09	48,200 52,900 60,800	690 450	684 450	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.160	
	* DVF-23SMH (左排気)		'77	29,800	630 390	600 372	φ 150	363	410	358	275.5	130	272	86	394	288	—	230		
	* DVF-23SMH ₂ (左排気)		'79	29,800 34,200	630 390	600 372	φ 150	363	410	358	275.5	129	272	86	394	288	—	230		
	* DVF-23SMH ₃ (左排気)		'82	34,200	630 390	600 372	φ 150	363	410	358	275.5	129	272	86	394	288	—	230		
	* DVF-23MH (左排気)		'85	34,200 36,600	678 426	648 414	φ 150	363	410	358	289	129	271.8	86.2	403	—	185.5	243		
	廃 止		'93																	

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考			
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d					
23 cm	DVF-23MQ		'85	38,600 41,300	750 492	726 474	φ 150	363	410	358	289	129	86.2	271.8	403	—	185.5	243	P.160			
	DVF-23MRQ		'93	41,800 46,000	750 492	726 474	φ 150	363	420	358	274	152	71	287	403	—	223	280				
	DVF-23MRQs		'09	50,600 51,800 53,000 61,000	750 462	726 450	φ 150	363	420	358	274	152	71	287	403	—	223	280				
	* DVF-23MQH (左排気)		'85	38,600 41,300	750 492	726 474	φ 150	363	410	358	289	129	271.8	86.2	403	—	185.5	243				
	廃 止		'93																			
	DVF-23MX		'85	43,800	480	468	φ 150	363	410	358	274	129	86.2	271.8	403	—	185.5	243				
	DVF-23MRX		'93	43,800 48,200	480	468	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.160			
	DVF-23MRXs		'09	53,000 63,600	480	468	φ 150	363	420	358	274	152	71	287	403	—	223	280				
	* DVF-23BLM		'80	36,800 41,800	570 372	534 348	φ 150	363	410	358	275.5	129	86	272	394	288	—	230				
	* DVF-23BLMs		'82	41,800	570 372	534 348	φ 150	363	410	358	275.5	129	86	272	394	288	—	230	DVF-23MRs+DV-232F			
	DVF-23MB		'86	41,800 44,200	630 360	606 348	φ 150	363	410	358	289	129	86.2	271.8	403	—	185.5	243				
	廃 止		'07																			
	* DVF-23BLH		'80	36,800 41,800	570 372	534 348	φ 150	363	410	358	275.5	129	272	86	394	288	—	230				
	* DVF-23BLHs		'82	41,800	570 372	534 348	φ 150	363	410	358	275.5	129	272	86	394	288	—	230				
	DVF-23MHB		'86	41,800 44,200	630 360	606 348	φ 150	363	410	358	289	129	271.8	86.2	403	—	185.5	243				
	廃 止		'11																			
	DVF-23MQB		'86	43,600	648 420	660 408	φ 150	363	410	358	289	129	86.2	271.8	403	—	185.5	243				
	DVF-23MQBs		'92	46,300	657 420	633 408	φ 150	363	410	358	289	129	86.2	271.8	403	—	185.5	243				
	廃 止		'07																● DVF-23MRs+DV-232F ● BL 無し			
	DVF-23MQHB		'86	43,600	648 420	660 408	φ 150	363	410	358	289	129	271.8	86.2	403	—	185.5	243				
	DVF-23MQHBs		'92	44,800	657 420	633 408	φ 150	363	410	358	289	129	271.8	86.2	403	—	185.5	243				
	廃 止		'07																			
	DVF-23P (シルキーホワイト) DVF-23PC (ブラウン)		'85	43,800 44,800	624 420	600 402	φ 150	363	410	385 357.5	289	129	86	272	—	—	—	—			●フラットインテリア パネルタイプ DVF-T23FVD もあります。	
	DVF-23PR (シルキーホワイト)		'93	44,800	684 426	642 414	φ 150	363	418	358	274	152	71	287	403	—	223	280				
	DVF-23PDs		'01	44,800 49,300	600 480	570 450	φ 150	363	418	358	274	152	71	287	403	—	223	280				
	DVF-23PDs		'09	54,200	600 480	570 450	φ 150	363	418	358	274	152	71	287	403	—	223	280	P.208	風量小		
	DVF-XT23D DV-X23P 別売ルーバー		'16	44,200 47,400 54,500 11,300 12,300 13,500	595 475	550 440	φ 150	363	418	358	274	152	70	288	403	—	223	280				
	DVF-23FPX		'93	46,800	636 382	600 354	φ 150	363	418	358	274	152	71	287	403	—	223	280				
	DVF-23FPDs		'01	46,800 51,500	600 290	570 280	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.169	風量・騒音注意		
	DVF-23FPDs		'09	56,700	600 480	570 450	φ 150	363	420	358	274	152	71	287	403	—	223	280				
	DVF-T23FVD		'16	52,600 58,500 67,300	595 475	550 440	φ 150	363	420	358	274	152	70	288	403	—	223	280				
	DVF-23FPDAs		'03	46,800 51,500	600 290	570 280	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.209	風量・騒音注意		
DVF-23FPDAs		'09	56,700	600 290	570 280	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-XT23DA DV-X23FV 別売ルーバー		'15	46,400 49,600 57,000 9,400 12,300 13,500	595 265	550 245	φ 150	363	420	358	274	152	70	288	403	—	223	280					
DVF-23FPQX		'93	49,800	695 372	670 372	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.169	風量・騒音注意			
DVF-23FPQDs		'01	49,800 54,800	700 550	670 520	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-23FPQDs		'09	60,300	700 550	670 520	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-T23FVQDA		'16	57,000 59,100 68,000	660 300	595 275	φ 150	363	420	358	274	152	70	288	403	—	223	280		風量注意			
DVF-23RYDs		'01	44,800 49,300	600 480	570 450	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-23RYDs		'09	54,200	600 480	570 450	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-T23RVYDA		'16	54,400 56,800 65,300	635 280	580 260	φ 150	363	420	358	274	152	70	288	403	—	223	280	P.152				
DVF-23RDs		'01	42,800 44,000	600 480	570 450	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-23RDs		'09	48,400	600 480	570 450	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-T23RVD		'16	48,400 52,700 60,600	635 500	580 465	φ 150	363	420	358	274	152	70	288	403	—	223	280	P.165				
DVF-23RDAs		'03	42,800 44,000	600 290	570 280	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-23RDAs		'09	48,400	600 290	570 280	φ 150	363	420	358	274	152	71	287	403	—	223	280					
DVF-T23RVDA		'16	50,600 53,000 61,000	635 280	580 260	φ 150	363	420	358	274	152	70	288	403	—	223	280	P.165				

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			□A	B(B')	C	D	E	F	a	b	c	d		
23 cm	DVF-23RQD ₃	 '01	44,800 46,000	700 550	670 520	φ 150	363	420	358	274	152	71	287	403	—	223	280	P.165	● DVF-25PND ₁₀ + DV-20KT (片落管) にて代替
	DVF-23RQD ₈	 '09	50,600	700 550	670 520	φ 150	363	420	358	274	152	71	287	403	—	223	280		
	DVF-T23RVQDA	 '16	52,800 55,200 63,500	705 310	640 290	φ 150	363	420	358	274	152	70	288	403	—	223	280		
	DVF-23PND	 '01	53,800 61,800	600 480	570 450	φ 150	395	470	386	232	135	82.5	303.5	418	280 220	—	208		
	DVF-23PND ₈	 '09	68,000	600 480	570 450	φ 150	395	470	386	232	135	82.5	303.5	418	280 220	—	208		
	DVF-23PND ₉	 '13	68,000	600 480	570 450	φ 150	395	470	386	232	135	82	304	418	280 220	—	207		
	廃 止	'18																	
	DVF-23PNQD	 '01	55,800 63,900	700 550	670 520	φ 150	395	470	386	278	161.5	82.5	303.5	418	280 220	—	238		● DVF-25PND ₁₀ + DV-20KT (片落管) にて代替
	DVF-23PNQD ₈	 '09	70,300	700 550	670 520	φ 150	395	470	386	278	161.5	82.5	303.5	418	280 220	—	238		
	DVF-23PNQD ₉	 '13	70,300	700 550	670 520	φ 150	395	470	386	278	162	82	304	418	280 220	—	237		
	廃 止	'18																	
	DVF-23FPN	 '93	59,800	552 348	540 340	φ 150	363	420	358	274	152	71	287	403	—	223	280		● DVF-XT23QDA+DV-X23FV ● 消音構造無し、騒音注意
	DVF-23FPND ₃	 '01	59,800 65,800	552 348	540 340	φ 150	363	420	358	274	152	71	287	430	—	223	280		
	DVF-23FPND ₈	 '09	72,400	552 348	540 340	φ 150	363	420	358	274	152	71	287	430	—	223	280		
	廃 止 (消音形)	'16																	
	DVF-T23LYDA	 '16	54,200 60,800 69,900	635 280	580 260	φ 150	363	420	358	274	152	70	288	403	—	223	280	P.151	
DVF-XT23YDA	 '15	50,200 56,300 64,700	—	—	φ 150	363	—	358	274	152	70	288	403	—	223	280	P.197	●別売ルーバー(本体カバー)が必要	
DVF-XT23QDA	 '15	48,600 49,900 57,400	—	—	φ 150	363	—	358	274	152	70	288	403	—	223	280	P.210	●別売ルーバー(本体カバー)が必要	
DVF-23PUD	 '02	66,000 72,600	240 180	240 170	φ 150	395	470	386	257	161.5	82.5	303.5	422	—	—	241	P.172	結気専用	
DVF-23PUD ₈	 '09	79,900 81,500 93,700	240 180	240 170	φ 150	395	470	386	257	161.5	82.5	303.5	422	—	—	241			
25 cm	DVF-25PND	 '01	59,800 67,800	800 600	750 570	φ 200	395	470	386 (392)	278	161.5	82.5	393.5	418	280 220	—	238		
	DVF-25PND ₈	 '09	74,600	800 600	750 570	φ 200	395	470	386 (392)	278	161.5	82.5	393.5	418	280 220	—	238		
	DVF-25PND ₉	 '13	74,600	800 600	750 570	φ 200	395	470	386 (392)	278	162	82	304	418	280 220	—	237		
	DVF-25PND ₁₀	 '18	74,600 84,500 97,200	800 600	750 570	φ 200	395	470	386 (392)	278	162	82	304	418	280 220	—	237	P.171	●センターパネル交換不可
	DVF-25FPD	 '01	49,800 57,000	800 600	750 570	φ 200	395	475	386 (392)	278	161.5	82.5	303.5	418	200	—	238		
	DVF-25FPD ₈	 '09	62,700	800 600	750 570	φ 200	395	475	386 (392)	278	161.5	82.5	303.5	418	200	—	238		
	DVF-25FPD ₉	 '13	62,700	800 600	750 570	φ 200	395	475	386 (392)	278	162	82	304	418	200	—	237		
	DVF-25FVD ₁₀	 '18	62,700 67,600 77,700	800 600	750 570	φ 200	395	475	386 (392)	278	162	82	304	418	200	—	237	P.171	
	DVF-25RVD	 '18	56,600 60,500 69,600	800 600	750 570	φ 200	395	475	386 (392)	278	162	82	304	418	200	—	237	P.166	
2 部 屋 用	* DVP-10BL	'78	14,600 16,800	93	84	φ 100	175	225	170	200	115	85	85	212	75	—	200		
	DVP-10F	'85	16,800	84	69	φ 100	175	225	168	200	119	84	84	212	—	164	222		
	DVP-10F ₂	 '91	16,800 17,600	84	69	φ 100	175	225	168	197	118.5	84	84	212	—	168	226		
	DVP-10FH	 '93	17,600	84	69	φ 100	175	244	168	197	118.5	84	84	212	—	168	226		
	DVP-G10FH	 '95	17,600	94	96	φ 100	175	244	168	197	119.5	84	84	204	204	—	146		
	DVP-G10L ₃	 '02	17,600	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVP-G10L ₄	 '08	18,700	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVP-G10L ₈	 '09	20,600	85	87	φ 100	175	246	168	197	119.5	84	84	204	204	—	146		
	DVP-T10L	 '18	21,600 21,800 25,100 28,900	87	87	φ 100	175	246	172 (171)	185	119.5	85.5	85.5	204	204	—	146	P.155	
	DVP-S10FH	 '95	17,600	88	91	φ 75	175	244	168	197	119.5	84	84	204	204	—	146		
	DVP-S10FH ₁	 '97	17,100	88	91	φ 75	175	244	168	197	119.5	84	84	204	204	—	146		
	DVP-S10FH ₄	 '08	18,200 21,000 25,100 28,900	88	91	φ 75	175	244	168	197	119.5	84	84	204	204	—	146	P.157	
	* DVP-14G	'73	15,600	126	138	φ 100	225 x 232	273	222	182	124	176	46	—	—	—	—		●DVP-T14L ●注意：埋込寸法など異なる
	廃 止	'76																	
	* DVP-14S	'77	15,600	144	144	φ 100	225	270	220	193.5	135.5	50.5	169.5	—	—	—	—		
	* DVP-14S ₂	'79	15,600 17,800	144	144	φ 100	225	270	220	199.5	134.5	50.5	169.5	—	—	—	—		
DVP-14F DVP-14FA (右側吸込) DVP-14FC (左側吸込)	 '85	17,800	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222			
DVP-14F ₂	 '91	17,800 18,700	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222			
DVP-14FH	 '93	18,700	168	162	φ 100	225	290	217	200	107.5	108.5	108.5	265	138	168	226			
DVP-G14FH	 '95	18,700	177	171	φ 100	225	290	217	198	119.5	108.5	108.5	253	253	—	146			
DVP-G14L ₃	 '02	18,700	162	162	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146			
DVP-G14L ₄	 '08	20,200	162	162	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146			
DVP-G14L ₈	 '09	22,200	162	162	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146			
DVP-T14L	 '18	22,300 25,600 29,400	175	174	φ 100	225	293	221.5 (220)	200	119.5	110	110	253	253	—	146	P.155		

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。




色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
2 部 屋 用 14 cm	DVP-14FQ DVP-14FQA (右側吸込) DVP-14FQC (左側吸込)	'85	19,800	198	198	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVP-14FQ ₂	'91	19,800 20,100	198	198	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVP-14FHQ	'93	20,100	198	198	φ 100	225	290	217	200	107.5	108.5	108.5	265	138	168	226		
	DVP-G14FHQ	'95	20,800	209	201	φ 100	225	290	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-G14LQ ₃	'02	20,800	204	200	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-G14LQ ₄	'08	22,000	204	200	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-G14LQ ₈	'09	24,200	204	200	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-T14LQ	'18	24,200 27,700 31,900	205	206	φ 100	225	293	221.5 (220)	200	119.5	110	110	253	253	—	146	P.155	
	DVP-14FP (高静圧タイプ)	'89	18,200	168	168	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		●DVP-TD14CLDT ●電源接続注意 ●プラスチック製
	廃 止	'90																	
	* DVP-14BL	'81	20,000	162	150	φ 100	225	270	220	199.5	134.5	50.5	169.5	260	—	—	209.5		
	DVP-14FB DVP-14FAB (右側吸込) DVP-14FCB (左側吸込)	'86	20,000	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVP-14FB ₂ DVP-14FAB ₂ (右側吸込) DVP-14FCB ₂ (左側吸込)	'89	20,000	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVP-14FB ₂	'91	20,000	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVP-14FB ₃	'92	21,000	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVP-G14FHB	'98	20,700	160	157	φ 100	225	290	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-G14L ₃ B	'06	20,700	162	162	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-G14L ₃ B ₁	'16	25,600	162	162	φ 100	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-T14LQB	'19	26,800 30,500 35,100	205	206	φ 100	225	293	221.5 (220)	200	119.5	110	110	253	253	—	146	P.225	2 極接地形差込みプラグ
	DVP-14FQB DVP-14FQAB (右側吸込) DVP-14FQCB (左側吸込)	'89	21,900	204	204	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	DVP-14FQB ₃	'91	21,900 23,000	204	204	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	168	226		
	DVP-G14FHBQ	'98	22,700	201	195	φ 100	225	290	217	198	119.5	108.5	108.5	253	253	—	146		
	廃 止	'07																	
	DVP-14H	'89	17,800 18,700	165	165	φ 100	225	290	217	205	109	108.5	108.5	—	—	—	—		
	DVP-G14H	'95	19,000	177	171	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CL ₃	'02	19,000	175	175	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CL ₄	'08	20,500	175	175	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CL	'14	20,500 22,000 23,600 27,100	180	180	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.144	
	DVP-14HQ	'89	19,800 20,100	186	192	φ 100	225	290	217	205	109	108.5	108.5	—	—	—	—		
	DVP-G14HQ	'95	21,000	209	201	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLQ ₃	'02	21,000	200	200	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLQ ₄	'08	22,300	200	200	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLQ	'14	22,700 24,000 25,600 29,400	210	210	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.144	
	DVP-G14CLE ₃	'02	31,000	175	175	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLE ₄	'08	33,500	175	175	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CL DV-14CES 別売品 DV-14ACMD 別売品	'12	20,500 22,000 23,600 27,100 8,500 9,400 10,300 15,700 17,300 19,000	180	180	φ 100	225	293	221.5 (223)	200	120	111.5	111.5	243	243	—	146	P.144	●廃止機種の排気口を残し本体と中間取付形電動シャッターにて買替取付可能
	DVP-G14CLQE ₃	'02	33,000	200	200	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLQE ₄	'08	35,000	200	200	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLQ DV-14CES 別売品 DV-14ACMD 別売品	'12	22,700 24,000 25,600 29,400 8,500 9,400 10,300 15,700 17,300 19,000	210	210	φ 100	225	293	221.5 (223)	200	120	111.5	111.5	243	243	—	146	P.144	●廃止機種の排気口を残し本体と中間取付形電動シャッターにて買替取付可能
	DVP-G14CLDA ₃	'03	23,500 25,800	175 180	175 178	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLDA	'14	26,400 28,400 32,700	182	180	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.145	

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
2 部 屋 用	DVP-G14CLDRA ₃	'05	29,500	175 70	175 70	φ 100	225	293	217	228	120	108.5	108.5	243	243	—	146		●壁スイッチ変更及び配線本数の追加工事必要。
	DVP-T14CLDA	'14	25,800 26,400 28,400 32,700	180 82	180 78	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.145	
	DVP-G14CLDK ₃	'03	23,500	175 110	175 110	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		●壁スイッチ変更及び配線本数の追加工事必要。
	DVP-T14CLDK	'14	25,800 26,400 28,400 32,700	200 130	200 125	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.145	
	DVP-G14CLDX ₃	'09	23,800	135 84	135 84	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		風量大
	DVP-T14CLDA	'14	25,800 26,400 28,400 32,700	180 82	180 78	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.145	
	DVP-G14CLDRK ₃	'05	29,500	175 110	175 110	φ 100	225	293	217	228	120	108.5	108.5	243	243	—	146		●壁スイッチ変更及び配線本数の追加工事必要。
	DVP-T14CLDK	'14	25,800 26,400 28,400 32,700	200 130	200 125	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.145	
	DVP-T14CLDP	'14	30,400 30,700 34,500 39,700	215 132	210 130	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.146	
	DVP-14HB	'92	21,800	150	150	φ 100	225	293	217	210	109	108.5	108.5	255	226	—	211		
	DVP-G14HB	'98	21,200	177	171	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CL ₃ B	'06	21,200	175	175	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLB	'16	23,900 26,800 30,800	180	180	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.223	2極接地形差込みプラグ
	DVP-14HQB	'92	23,800	168	168	φ 100	225	293	217	210	109	108.5	108.5	255	226	—	211		
	DVP-G14HQB	'98	23,200	209	201	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLQ ₃ B	'06	23,200	200	200	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLQB	'16	25,900 27,500 31,600	200	200	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.223	2極接地形差込みプラグ
	DVP-G14CLDA ₃ B	'06	26,000	175 70	175 70	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-T14CLDKB	'16	28,900 31,800 36,600	200 130	200 125	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.223	3極接地形差込みプラグ
	DVP-T14CLDKBH	'16	31,300 34,200 39,300	200 130	200 125	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.223	3極接地形差込み引掛プラグ
	DVP-T14LB	'19	25,600 28,700 33,000	175	174	φ 100	225	293	221.5 (220)	200	119.5	110	110	253	253	—	146	P.225	2極接地形差込みプラグ
	* DVP-14SL	'85	25,400	144	144	φ 100	225	270	270	199.5	134.5	50.5	169.5	—	—	—	—		
	DVP-14SL ₃	'85	27,800 30,600	168	162	φ 100	225	270	217	200	107.5	108.5	108.5	265	138	164	222		
	廃 止	'93																	
	DVP-S14FH	'95	18,700	153	153	φ 75	225	290	217	198	119.5	108.5	108.5	253	253	—	146		● DVP-T14L+DV-07KT (片落管)にて代替
	DVP-S14FH ₁	'97	17,700	153	153	φ 75	225	290	217	198	119.5	108.5	108.5	253	253	—	146		
	廃 止	'07																	
	DVP-S14FHQ	'95	20,800	181	177	φ 75	225	290	217	198	119.5	108.5	108.5	253	253	—	146		● DVP-T14LQ+DV-07KT (片落管)にて代替
	DVP-S14FHQ ₁	'97	19,800	181	177	φ 75	225	290	217	198	119.5	108.5	108.5	253	253	—	146		
	廃 止	'07																	
	DVP-S14FHP	'95	26,700	176 112	171 112	φ 75	225	293	217	198	119.5	108.5	108.5	253	253	—	146		
	DVP-S14FHP ₁	'97	23,700	176 112	171 112	φ 75	225	293	217	198	119.5	108.5	108.5	243	243	—	146		
	廃 止	'00																	
	DVP-S14H	'95	19,000	153	153	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		● DVP-T14CL+DV-07KT (片落管)にて代替
	DVP-S14H ₁	'97	18,000	153	153	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
	廃 止	'07																	
	DVP-S14HQ	'95	21,000	177	181	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		● DVP-T14CLQ+DV-07KT (片落管)にて代替
	DVP-S14HQ ₁	'97	20,000	177	181	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
	廃 止	'07																	
	DVP-S14HP	'95	26,700	176 112	171 112	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-S14HP ₁	'97	23,700	176 112	171 112	φ 75	225	293	217	198	120	108.5	108.5	243	243	—	146		
	廃 止	'07																	
	* DVP-18SB、SA、SC	'81	19,800	180	174	φ 100	275	322.5	270	198.5	133.5	61.5	208.5	311	—	—	226		●アタッチメント(DV-18PA) を使用し、DVP-T14CLQにて 代替(プラスチックボディー)
	廃 止	'85																	
	* DVP-18BL	'82	20,500	174	168	φ 100	275	322.5	270	198.5	133.5	61.5	208.5	311	—	—	226		●アタッチメント(DV-18PA) を使用し、DVP-T14CLQBにて 代替(プラスチックボディー)
	廃 止	'89																	
2 部 屋 用 (14 cm)	DVP-G14HT	'95	31,800	225 135	216 135	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLT ₃	'02	31,800	215 135	210 135	φ 100	225	293	217	198	120	108.5	108.5	243	243	—	146		
	DVP-G14CLT ₄	'08	33,000	215 135	210 135	φ 100	225	293	217	228	120	108.5	108.5	243	243	—	146		
	DVP-T14CLDPT	'14	36,200 36,600 46,400 53,400	215 132	210 130	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.147	

- マークはカートリッジ式排気口採用機種です。
- ダクト用の*印機種は埋込寸法・排気口位置などが現行機種と違いますので、交換時確認してください。
- 右図は機種により形状が異なります。



色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			A	B(B')	C	D	E	F	a	b	c	d		
2 5 14 cm 部 屋 用	DVP-G14CLRT ₃	'05	41,800	215 135	210 135	φ 100	225	293	217	228	120	108.5	108.5	243	243	—	146		●壁スイッチ変更及び配線本数の追加工事必要。
	DVP-T14CLDPT	'14	36,200 46,400 53,400	212 132	210 130	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.147	
	DVP-TD14CLDT	'14	41,900 48,200	270 160	270 160	φ 100	225	293	221.5 (223)	200	107.5	111.5	111.5	243	243	—	146	P.133	
3 部 屋 用	* DVP-18SB-AB * DVP-18SB-BC	'85	20,400	168	162	φ 100	275	322.5	270	196	133.5	73.5	196.5	—	—	—	—		●アタッチメント(DV-18PA)を使用し、DVP-T14CLDPTにて代替(プラスチックボディ)
	廃 止	'95																	
2 1 3 部 屋 用	DVP-20CLTS ₃	'04	34,800	250 165	250 156	φ 100	316	380	309	200	120	154.5	154.5	325	325	—	146		P.148
	DVP-20CLTS ₄	'08	36,800 41,300 46,400 53,400	250 165	250 156	φ 100	316	380	309	200	120	154.5	154.5	325	325	—	146		
中 間 形	DVC-12S	'76	13,000	135	138	φ 100	—	146 × 214	—	176	—	—	—	170 210	—	—	—		P.216
	DVC-12S ₁	'77	13,000 14,400	135	138	φ 100	—	146 × 214	—	176	—	—	—	170 210	—	—	—		
	DVC-12TSB	'88	15,800 18,200	102	114	φ 100	—	162 × 205	136 × 153	160	—	—	—	170 210	—	—	—		
	DVC-12TSB ₁	'16	19,300 21,200 24,400	104	116	φ 100	—	162 × 205	136 × 153	160	—	—	—	170 210	—	—	—	P.216	DVC-12TSB ₁ (BL 無し)
	DVC-12BL	'78	13,000 14,800	99	102	φ 100	—	146 × 214	—	176	—	—	—	170 210	—	—	—		
	DVC-12TBL	'89	14,800 16,500	102	108	φ 100	—	162 × 205	136 × 153	160	—	—	—	170 210	—	—	—		
	廃 止 (BL 品)	'07																	
	DVC-15TSB	'84	19,800 21,800 25,100	114	108	φ 100	—	□260	□230	175	—	—	—	325 355	—	—	—		
	廃 止	'17																	
	DVC-12M ₃	'03	17,800	95	95	φ 100	—	193 × 185	157.5 × 185	163	—	—	—	185	—	—	—		P.214
	DVC-12M ₄	'06	17,800	95	95	φ 100	—	193 × 185	157.5 × 185	163	—	—	—	185	—	—	—		
	DVC-12M ₅	'13	17,800 18,300 21,000	95	95	φ 100	—	193 × 185	157.5 × 185	163	—	—	—	185	—	—	—		
	DVC-13M ₃	'03	23,200	105	103	φ 100	—	264	201 × 198	212	—	—	—	238	—	—	—		P.214
	DVC-13M ₄	'06	23,200	105	105	φ 100	—	268	201 × 198	219	—	—	—	238	—	—	—		
	DVC-13M ₅	'13	23,200 23,900 27,500	105	105	φ 100	—	268	208	219	—	—	—	238	—	—	—		
	DVC-15M ₃	'03	28,500	195	200	φ 100	—	313	248	220	—	—	—	285	210	—	—		P.214
	DVC-15M ₄	'06	28,500	195	200	φ 100	—	313	248	220	—	—	—	285	210	—	—		
	DVC-15M ₅	'13	28,500 29,400 33,800	195	200	φ 100	—	313	254	220	—	—	—	285	210	—	—		
	DVC-18M ₃	'03	32,800 33,800 38,900	260 170	250 150	φ 100	—	380	—	229	—	—	—	315	210	—	—	P.215	P.215
	DVC-18MQ ₃	'03	35,800 36,900 42,400	300 210	300 190	φ 100	—	380	—	229	—	—	—	315	210	—	—		
	DVC-18ME ₃	'03	56,000	240 140	240 135	φ 100	—	380	—	229	—	—	—	315	210	—	—		
	廃 止	'12																	●DVC-18M ₃ (電気シャッターなし)
	DVC-18MEA ₃	'04	56,000	240 135	240 130	φ 100	—	380	—	229	—	—	—	315	210	—	—		
	廃 止	'12																	
	DVC-18TSB	'84	22,800 23,800 27,400 29,000 31,900 36,700	174	183	φ 100	—	340	310	192	—	—	—	405 435	315 345	—	—	P.217	P.218
	DVC-18T	'82	23,000 25,800	192	204	φ 100	—	340	310	192	—	—	—	405 435	315 345	—	—		
	DVC-18T ₁	'07	31,000 32,900 36,200 41,600	192	204	φ 100	—	340	310	192	—	—	—	405 435	315 345	—	—		
	DVC-18ABL DVC-18BBL DVC-18CBL	'83	24,400 26,800	140	134	φ 100	—	340	310	192	—	—	—	405 435	315 345	—	—		●DVC-18T ₁ (BL 無し・2～3部屋用)
	廃 止 (BL品・2部屋用)	'07																	
	DVC-18TA DVC-18TB DVC-18TC	'82	23,000 25,300	194	204	φ 100	—	340	310	192	—	—	—	405 435	315 345	—	—		
	廃 止 (2部屋用)	'07																	●DVC-18T ₁ (2～3部屋用)

色は現行機種です。価格は消費税抜価格で表示されています。表内寸法はmm単位で表記しています。

タイプ	形 名	発売年	希望小売価格 (円)	風量 (m³/h)		接続 パイプ径 (mm)	埋込 寸法 (mm)	寸法比較 (mm)						天吊寸法 (mm)				掲載頁	備 考
				50Hz	60Hz			□ A	B(B')	C	D	E	F	a	b	c	d		
中 間 形	DVC-20TR	'88	15,900 '92 17,800 '07 21,400 '20 22,700 '22 25,000 '23 28,800	204	222	φ 150	—	φ 228 × 195	—	238.5	—	—	—	245.5	—	—	—	P.217	
	DVC-20TRQ	'88	20,500 '92 22,800 '07 27,400 '20 29,000 '22 31,900 '23 36,700	261	297	φ 150	—	φ 228 × 195	—	238.5	—	—	—	245.5	—	—	—	P.217	
	DVC-20TA DVC-20TB DVC-20TC	'82	24,400 '92 35,000	246 180	258 180	φ 100	—	340	310	192	—	—	—	405 ~ 435	315 ~ 345	—	—		
	廃 止 (2部屋用)	'07																	
	DVC-20T	'82	31,800 '92 35,000	246 180	258 180	φ 100	—	340	310	192	—	—	—	405 ~ 435	315 ~ 345	—	—		
	DVC-20T ₁	'07	42,000	246 180	258 180	φ 100	—	340	310	192	—	—	—	405 ~ 435	315 ~ 345	—	—		
	廃 止	'12																	
	DVC-20S	'79	26,800 '80 30,600 '92 32,500 '07 42,300	402	414	φ 150	—	324 × 416	—	240	—	—	—	346 ~ 400	360	—	—		
	廃 止	'17																	
	DVC-23S	'79	29,800 '80 33,000 '92 35,800 '07 46,600	660	642	φ 150	—	415 × 466	—	240	—	—	—	436 ~ 490	410	—	—		
	廃 止	'17																	
	DVC-18HN	* '00	44,000 '07 51,600 '23 59,300	310	300	φ 150	—	450 × 280	—	271	—	—	—	330 (272)	350	—	—	P.219	
	DVC-20HN	* '00	50,000 '07 58,200 '23 66,900	450 290	450 280	φ 150	—	450 × 280	—	277	—	—	—	330 (272)	350	—	—	P.219	
	DVC-23HN	* '00	54,000 '07 63,400 '23 72,900	600 420	610 370	φ 150	—	500 × 320	—	296	—	—	—	370 (292)	400	—	—	P.219	
	DVC-25HN	* '00	64,000 '07 74,700 '23 85,900	730 460	700 400	φ 200	—	500 × 320	—	296	—	—	—	370 (292)	400	—	—	P.219	
	DVC-18H	* '00	31,000 '07 36,500 '23 42,000	310	300	φ 150	—	450 × 280	—	271	—	—	—	330 (272)	350	—	—	P.220	
	DVC-20H	* '00	37,000 '07 43,200 '23 49,700	450 290	450 280	φ 150	—	450 × 280	—	277	—	—	—	330 (272)	350	—	—	P.220	
	DVC-23H	* '00	41,000 '07 48,200 '23 55,400	600 420	610 370	φ 150	—	500 × 320	—	296	—	—	—	370 (292)	400	—	—	P.220	
	DVC-25H	* '00	50,000 '07 58,000 '23 66,700	730 460	700 400	φ 200	—	500 × 320	—	296	—	—	—	370 (292)	400	—	—	P.220	